



Product Data Sheet

GEC-8VARHUB-4

Multi-Channel UTP Active Receiver Hubs

Overview

Featuring UTC FS' Automatic Video Compression (AVC) technology, these active receiver hubs incorporate a sophisticated microprocessor-controlled analog circuit. With this innovative technology, these units can continuously analyze incoming video signals and compensate for cable attenuation independent of video signal content.

The active receiver hubs provide high-resolution color or black and white video over unshielded twisted pair wires at distances up to 6,000 feet (1830 m). In addition, the UTP connection is supported by a standard detachable terminal block or EIA/TIA 568B compliant RJ-45 adapter (included).



Standard Features

- Automatic Video Compensation (AVC) technology delivers high quality video without adjustment
- Up to 4,000 feet (1220 m) transmission range
- NTSC, PAL and SECAM compatibility for optimum flexibility
- Video present LED for each channel provides convenient diagnostic help
- Built-in auto-range AC power supply compatible with virtually all AC voltages. Excludes 4 channel model.
- 70dB crosstalk and noise immunity
- Ground loop immunity
- Surge protection protects connected video equipment
- 1U high wall or rack mountable reduces requires less CCTV rack space
- Includes 8, 16 or 32 coax jumper cables to save time and money. Excludes GEC-4VARHUB-4.
- 8 and 16 channel models include x4 and x2 distribution amplifier

GEC-8VARHUB-4

Multi-Channel UTP Active Receiver Hubs

Specifications

Video

- Channel: 8
- Video Present: One green LED per channel
- Conditioning: 0.7 to 1.4 V p-p video accepted
- Frequency: 20 to 6 MHz
- Format: PAL, SECAM, NTSC
- Twisted Pair: 100 Ohms +/- 20%, 24 AWG minimum, unshielded Category 2-7
- Coax Impedance: 75 Ohm
- Insertion Loss: 0.3 dB
- CTaNI/CMRR: 70 dB
- Surge Protection: built-in
- Outputs per input: 4

Connectors

- Video Connector: BNC
- UTP Connector: Terminal blocks with RJ-45 adaptor option
- Included Jumper Cables: 32

Miscellaneous

- Power Indicator: Red LED
- Operating Temperature: -10°C to +50°C
- Storage Temperature: -30°C to +70°C
- Relative humidity: 0 to 95%, non-condensing
- Dimensions (W x H x D): 435 x 42 x 203 mm
- Weight: 2040 gr
- Material: Extruded Aluminum and sheet metal
- Mounting Brackets: Included
- Input voltage: 80 to 240 VAC

Diagram

Ordering Information

GEC-8VARHUB-4

8-CH Active Receiver, w/ Surge Protection & GL isolation,
70dB CTaNI, RJ-45 and Screw Terminal Block, w/ AVC,
4,000 ft. < 1.220m>

