

ET4200 Series

Unmanaged Industrial 4-port 10/100/1000Base-TX Ethernet Switch



OT Systems' Unmanaged Switch offers an easy and affordable solution for network managers to connect four 10/100/1000Mbps Ethernet. The Unmanaged Switch uses a high performance auto-sensing exchange chip for full functionality of transfer and exchange, guaranteeing the safety and stability of data transfer.

Features

- Connect four 10/100/1000Base-TX
- Auto-Negotiation or manual mode setting of speed and duplex mode
- MDI/MDI-X Auto-Crossover supported
- Plug-and-Play / Hot-swappable
- Store and forward switching mechanism
- Wall-mount or operate in ET-C12 rack mount chassis

Ordering Information

Model	Description	
ET4200-YY	Unmanaged Industrial 4-port 10/100/1000Base-TX Ethernet Switch	
(YY) =	Installation	Power Adapter
SA	Standalone Wall-mount	ET-PA/12V. 1.25A 12VDC Power Adapter (<i>Included</i>). DC Jack. (US, European, UK or Australian power plug available)
CM	Card Module	From ET-C12 chassis (<i>Purchase Separately</i>)

NOTE: Please feel free to consult factory for any special requirement and customization.

ET4200 Series

Specifications

Ethernet

Standards:	IEEE802.3 10BASE-T IEEE802.3u 100BASE-TX IEEE802.3ab 1000BASE-T IEEE802.3x
Processing Type:	Store and forward Half-duplex back-pressure and IEEE802.3x Full-duplex flow control
Forward and Filter Rate:	14,881pps (10Mbps) 148,810pps (100Mbps) 1,488,100pps (1000Mbps)
Cabling:	10/100/1000Base-TX: Cat5 or above
Maximum Distance:	Cat5 UTP up to 100m
Connector:	4 x RJ45
Address Table Size:	2048MAC addresses

Electrical and Mechanical

Input Power:	12VDC
Power Consumption:	2.5W Max. 0.21A@12VDC
LED Indicators:	
Power:	Power Status
10/100/1000TX (Per Port):	Link/Activity, Full-duplex/Collision, Speed
Dimensions (WxDxH):	SA: 122 X 103 X 30 mm CM: 130 X 111 X 31mm
Weight:	SA: 0.33Kg (0.43Kg including PA) CM: 0.33Kg
Casing:	Aluminum case
Mounting Options:	Wall-mount Card module (in ET-C12 rack mount chassis)

Environmental

Operating Temperature:	-20°C to 60°C (-4°F to 140°F) Tested -40°C to 70°C (-40°F to 158°F)
Storage Temperature:	-40°C to 85°C (-40°F to 185°F)
Relative Humidity:	0% to 95% non-condensing

Regulatory Approvals

ISO9001
FCC Class A
EN55022: 2006 Class A
EN55024: 1998 + A1: 2001 + A2: 2003