

▶ 22" MULTITOUCH LCD DISPLAY

TX-22



LED 

▶ FEATURES

- Incorporates Projected Capacitive Touch Technology
- Multi-touch capabilities for systems with Microsoft® Windows® 7
- IPS Panel provides consistent and accurate colour from all viewing angles
- IP54 rating (front side) protects screen from splashing liquids and dust
- 1920 x 1080 Full HD resolution
- Flush touch screen makes surface neat and clean
- Tilt capacity from - 5° to 90°
- Dual inputs: VGA and DVI
- HID compliant for easy integration with thin client or computer
- Durable metal housing
- Rugged base design for superb stability
- Touch methods: Fingers or magnetic ball pens
- Lockable OSD buttons
- Perfect for public and interactive environments

▶ SPECIFICATION

Panel	Panel Type	LED-Backlit TFT LCD (IPS Panel)
	Panel Size	21.5"
	Max. Resolution	1920 x 1080
	Refresh Rate	60 Hz
	Pixel Pitch	0.248 mm
	Brightness	250 cd/m ² (Typical)
	Contrast Ratio	1,000 : 1 (Typical)
	Viewing Angle (H/V)	178°/178° (Typical)
Frequency (H/V)	H.Freq	31.47kHz – 82.3kHz
	V.Freq	56Hz – 75Hz
Input	VGA	15-Pin D-Sub
	DVI	24-Pin DVI-D
Touch Screen	Technology	Projected Capacitive
	Positioning Accuracy	±2.5mm
	Active Force	None required
	Panel Interface	USB (Type-B, HID compliant)
Power	DC output	12V/4.16A
	Power Consumption	100 - 240V, 50 - 60Hz
		< 27 (On) < 2W (Stand-by) < 1W (Off)
Operating Conditions	Temperature	0°C ~ 40°C (32°F~104°F)
	Humidity	20%~80% (No condensation)
Storage Conditions	Temperature	-20°C ~ 60°C (-4°F~140°F)
	Humidity	10%~90% (No condensation)
Mounting	VESA FPMPMI	Yes (100mm x 100mm)
Certificate	Regulations	FCC, CB, CE, BSMI
Dimensions	With base (W x H x D)	517 x 352 x 219 mm (20.4" x 13.9" x 8.6")
Net Weight	With base	6.9 kg (15.2 lbs)
	Packaging weight	9.9 kg (21.8 lbs)

All specifications are subject to change without prior notice



www.agneovo.com

Copyright © 2012 AG Neovo. All rights reserved.
The name AG Neovo is a trademark of Associated Industries China, Inc.
All other trademarks are the property of their respective owners.