


Powerful and intelligent PoE switch in a compact form factor for optimized utilization and efficiency



Power-over-Ethernet (PoE) technology brings simplicity and cost-savings to network deployment for all size of businesses. With more and more devices capable of receiving power over Ethernet, the PoE switches that can provide power to these end devices are in high demand. Traditional PoE switches come with high port density and are not flexible or optimized for small scale deployments. Users will end up with many unused ports. The Netgear ProSafe GS510TP provides a compact solution that fits nicely into a situation where low-port density is desired for specific areas or extension of the network. It comes with 8 PoE-capable Gigabit copper ports to connect to your PoE end devices and two additional dedicated Gigabit Fiber ports for uplinks with greater distance. Plus, with the PoE Plus support, GS510TP is able to provide sufficient power for those power-hungry devices with up to 30w per port with a total power budget of 130w on the switch. GS510TP is packed with powerful features capable of enhancing any type of business network.

The GS510TP comes with a comprehensive set of features, such as enhanced VLAN and QoS, access control lists (ACL), 802.1x port authentication, rate limiting and IGMP snooping and many more, to provide businesses with networks that are geared for growth while ensuring performance and reliability.



Features	Benefits
Power-over-Ethernet (PoE)	• Provide flexibility and simplicity for your VoIP and Video Surveillance deployments
PoE Plus	• Future-Proof, capable of powering your 11n WIFI access points as well as PTZ cameras and video phones
Traffic Management	• Prioritize traffic to ensure quality of latency-sensitive services and applications despite increasing traffic loads
Advanced Security with 802.1x and ACL	• User-based authentication and added filtering to permit or deny traffic based on MAC or IP addresses
Auto Voice and Auto Video	• Assist customers to easily set up VoIP or IP surveillance networks with a couple of simple steps
PoE Power Management	• Automatically detect PoE on the end devices and dynamically manage power assignments and priority
PoE Timer	• Schedule to turn off your WIFI network or VoIP phones outside of office hours for security and energy savings
Centralized Management via the New Smart Control Center	• Discover all the Smart Switches in the network, configure them from a central location; schedule mass configuration and firmware uploads

## Technical Specifications

### • Network Protocol and Standards Compatibility

- IEEE 802.3 10BASE-T
- IEEE 802.3u 100BASE-TX
- IEEE 802.3ab 1000BASE-T
- IEEE 802.3z 1000BASE-X
- IEEE 802.3x full-duplex flow control
- IEEE 802.3at (Power over Ethernet Plus)

### • Power Supply

- Power consumption: 147 W maximum
- 100-240VAC/50-60-Hz universal input
- PoE budget: 130W

### • Network Ports

- 8 10/100/1000 Mbps auto sensing Gigabit Ethernet
- 2 SFP slots

### • Physical Specifications

- Dimensions: (W x D x H):  
328 x 169 x 43 mm (12.91 x 6.65 x 1.7 in)
- Weight: 1.68 kg (3.7 lb)

### • Electromagnetic Emissions

- CE EN 55022, EN 61000 and EN 55024
- FCC Part 15 Class B
- VCCI Class B
- C-Tick

### • Environmental Specifications

- Operating temperature: 32° to 122° F (0° to 50° C)
- Storage temperature: -4° to 158° F (-20° to 70° C)
- Operating humidity: 90% maximum relative humidity, non-condensing
- Storage humidity: 95% maximum relative humidity, non-condensing
- Operating altitude: 10,000 ft (3,000 m) maximum
- Storage altitude: 10,000 ft (3,000 m) maximum

### • LEDs

- Per port (10/100 and Gigabit):  
Link/activity, speed
- Per device: Power, Fan, PoE Max
- Per PoE port: PoE Power, PoE fault

### • Safety

- UL/cUL 60950-1
- CE EN 60950-1
- CCC
- CB
- KCC

### • System Requirements

- Category 5 UTP Network cables or above
- Network card for each PC
- Network software (e.g., Windows®)
- Web browser (e.g., Internet Explorer 6.0 or higher, Netscape 6.0 or higher)

### • Administrative Switch Management

- IEEE 802.1Q static VLAN (64 groups, static)
- IEEE 802.1p Class of Service (CoS)
- Port-based QoS
- DSCP-based QoS
- DiffServ
- IEEE802.3ad link aggregation (manual or LACP)
- IEEE 802.1D Spanning Tree Protocol (STP)
- IEEE 802.1w Rapid Spanning Tree Protocol (RSTP)
- IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)
- IEEE 802.1ab Link Layer Discovery Protocol (LLDP)
- LLDP-MED
- SNMP v1, v2c, v3
- RFC 1213 MIB II
- RFC 1643 Ethernet interface MIB
- RFC 1493 bridge MIB
- RMON group 1, 2, 3, 9
- RFC 2131 DHCP client
- Voice VLAN

### – Auto-VOIP

- DHCP Filtering
  - Auto denial-of-service (DoS) protection
  - HTTP and HTTPS
  - Ping and traceroute
  - Power saving when link down
  - IEEE 802.1x
  - Port-based security by locked MAC addresses
  - IP and MAC ACL
  - Storm control for broadcast, multicast and unknown unicast packets
  - IGMP snooping v1/v2/v3
  - Protected Port
  - PoE Timer
  - Port-based ingress and egress rate limiting
  - STNP
  - Port mirroring support (many to one)
  - Web-based configuration
  - Configuration backup/restore
  - Password access control
  - RADIUS Support
  - TACACS+ support
  - Syslog
  - Firmware upgradeable
- ### • Performance Specifications
- Forwarding modes: Store-and-forward
  - Bandwidth: 20 Gbps
  - Network latency: <4μs for 64-byte frames in store-and-forward mode for 1000 Mbps to 1000 Mbps transmission
  - Buffer memory: 512KBytes per system
  - Address database size: 4,000 media access control (MAC) addresses per system
  - Addressing: 48-bit MAC address
  - Mean time between failures (MTBF): 458,124 hours at 25C (~52.3 years)
  - Acoustic noise: <38 dBA

**• Modules**

- AGM731F 1000BASE-SX SFP Module
- AGM732F 1000BASE-LX SFP Module
- AGM733 1000BASE-ZX SFP Module

**• Warranty**

- NETGEAR Lifetime Warranty

**• OnCall 24x7, Category 1**

- PMB0331-100 (US)
- PMB0331 (non-US)

**• Package Contents**

- ProSafe® 8-port PoE Smart Switch with 2 Gigabit SFP Ports (GS510TP)
- Rubber footpads
- Power cord
- Rack-mount kit
- Resource CD
- Installation guide

**• Ordering Information**

- North America: GS510TP-100NAS
- Europe: GS510TP-100EUS
- Asia & Japan: GS510TP-100AJS

**NETGEAR®**

350 E. Plumeria Drive  
San Jose, CA 95134-1911  
1-888-NETGEAR (638-4327)  
E-mail: [info@NETGEAR.com](mailto:info@NETGEAR.com)  
[www.NETGEAR.com](http://www.NETGEAR.com)

© 2012 NETGEAR, Inc. NETGEAR, the NETGEAR Logo, Connect with Innovation, PowerShift, and ProSafe are trademarks and/or registered trademarks of NETGEAR, Inc. and/or subsidiaries in the United States and/or other countries. Other brand names mentioned herein are for identification purposes only and may be trademarks of their respective holder(s). Information is subject to change without notice. All rights reserved.

This product comes with a limited warranty, the acceptance of which is a condition of sale. This product has been tested for quality assurance and this product or its components may have been recycled.

\*Basic technical support provided for 90 days from date of purchase.