


# TOSIBOX® | Central Lock



TOSIBOX® Central Lock user Interface

## TOSIBOX® Central Lock


TOSIBOX Central Lock can be serialized with a large number of TOSIBOX Keys and Locks. The connected devices can be bound to four different networks.

- Over 700 Mbit/s encryption throughput
- Up to 4000 concurrent connections from Keys or Locks
- Possibility to collect and view audit log data from connected TOSIBOX Lock devices
- Monitoring service for connected Locks and Sub Locks: get alerts of connect/disconnect events via e-mail
- All other existing features of the TOSIBOX Lock devices are also supported

### Technical data

- **Properties**
  - » One 1 Gbit/s WAN port
  - » Four 1 Gbit/s LAN ports
  - » Over 700 Mbit/s encryption throughput
  - » 1000 concurrent remote connections per LAN network
  - » Encryption and authentication PKI, 2048 bit RSA
  - » Data encryption TLS, AES-256-CBC / Blowfish-128-CBC
- **Physical properties**
  - » 1U (rack unit) for 19" rack cabinet (rack rails included)
  - » Length 430 mm / width 483 mm / height 43 mm
- **Environmental conditions**
  - » Operational temperature 10°C..30°C
  - » Humidity 20%..80% non-condensing
  - » Power consumption max 250 W
  - » Input voltage 90..264 V AC
  - » Input frequency 47..63 Hz
- **Other requirements**
  - » Requires one non-firewalled public IP address for Internet access

LAN 4 PORT  
LAN 3 PORT  
LAN 2 PORT  
LAN 1 PORT



SERVICE PORT  
WAN PORT