

Exceptional Performance and Stability

Samsung's SRN-4000 is a 64CH network video recorder that will allow the connection of up to 64 and 5MP cameras, 12 hot swap hard disc drives and redundant power supplies. While supporting high level functions such as RAID 5/6, 4 x gigabit ethernet ports and advanced video motion detection, it also supports a local monitor for ease of use, automatic camera registration, ONVIF cameras and mobile apps for smart phone and tablet connectivity.

SRN-4000

64CH 400Mbps Premium Network Video Recorder

- Up to 64CH and 5MP supported
- 400Mbps network camera recording
- Max. 12 Hot swap HDDs (RAID 5/6)
- VGA/HDMI local monitor
- Redundant hot swap power supply






Specifications

		SRN-4000
DISPLAY		
N/W Camera	Inputs	Up to 64CH
	Resolution	CIF ~ 5M
Live	Protocols	Samsung, ONVIF
	Local Display	HDMI / VGA
	Multi Screen Display	[Local monitor] 1 / 4 / 9 / 16 / Sequence, [Web] 1 / 4 / 9 / 16 / 32 / 64 / Sequence
PERFORMANCE		
Operating System	Embedded	Linux
	Compression	H.264, MPEG-4, MJPEG
Recording	Recording Bit Rate	Max. 400Mbps (2M 64camera real-time recording)
	Resolution	CIF ~ 5M
	Mode	Manual, Schedule (Continuous / Event), Event (Pre / Post)
	Event Trigger	Alarm input, Video loss, Camera event (Sensor, MD, Video Analytics), VA (Upto 4ch selectable, Advanced MD, Object classification (People, Car))
Search & Playback	Event Action	E-mail, PTZ preset, Alarm out, Buzzer, Monitor out
	Playback Bandwidth	25Mbps (16CH simultaneously)
	Search Mode	Date & Time (Calendar) / Event log list
	Simultaneous Playback	16CH (Local monitor, CMS), 4CH (Web)
Storage	Resolution	CIF ~ 5M
	Playback Function	Fast forward / backward, Move one step up / down
	Internal HDD	12 (Hot swap), Max. 36TB
Back up	External (e-SATA Interface)	NAS (iSCSI) : vesaRaid 1840i, Max. 192TB (JBOD)
	RAID	RAID-5/6
Sensor	File Back up (Via Web)	BU/Exe (GUI), JPG, AVI (Network)
	Function	Single channel play, Date-time/title display
Alarm	Input / Output	8 / 4 (NO/NC selectable)
	Input	64CH (Network)
Audio Communication	Compression	G.711, G.726
	Audio Communication	2-way
NETWORK		
Ethernet		RJ-45, Gigabit Ethernet x 4
Protocol Support		TCP/IP, UDP/IP, RTP (UDP), RTP (TCP), RTSP, NTP, HTTP, DHCP, PPPoE, SMTP, ICMP, IGMP, ARP, DNS, DDNS, UPnP, ONVIF, HTTPS, SNMP
DDNS		Samsung iPOLIS DDNS
Transmission Speed		Up to 200Mbps
Max. Remote Users		Search 3 / Live unicast 10 / Live multicast 20
IP		IPv4/v6
Security		IP address filtering, User access log, 802.1x authentication, Encryption
Language		English, French, German, Italian, Spanish, Russian, Turkish, Polish, Dutch, Swedish, Czech, Portuguese, Danish, Rumanian, Serbian, Croatian, Hungarian, Greek, Norwegian, Finnish, Korean, Chinese, Japanese, Thai
OS		Supported OS : Window XP (service pack 2 or above), Vista, 7, 8, Mac OS X (10.7 or above)
Web Browser		MS IE 8.x, 9.x, Google Chrome, Mac Safari, Firefox 2.x, 3.x
Viewer Software	Type	Webviewer, SmartViewer
	CMS Support	Support SDK / CGI
Smart Phone	Platform	Android, iOS
	Protocol Support	RTP, RTSP, HTTP, CGI
	Max. Remote Users	Live 10, Playback 1
FUNCTIONS		
Camera Setup	Register	Auto, Manual
	Setup Items	1) IP Address, Add Profile Edit, Bitrate, Compression, GOP, Quality 2) Video Setup (MD, ABF, Brightness/Contrast, Flip/Mirror, IRIS, WDR, D&N, SSNR, Shutter)
PTZ	Control	Via GUI, Webviewer
	Preset	256 presets
Smart phone	Support Model	I-Phone, Android
	Control	Live 4CH / Playback 1CH
System Control		Mouse
INDICATOR / INTERFACE		
Front	Indicator	LED status indicator : HDD action 12, RAID status 1, Alarm 1, Power 1, Record 1, Back up 1, Network 1
	Switch	PWR switch 1ea, Key-lock 1ea
Connections	VGA	1ea
	HDMI	1ea
	Audio	Out (1ea, RCA, Line)
	Ethernet	4 RJ-45 10/100/1000 Base-T
	Alarm	In (8ea, Terminal block) / Out (4ea, Terminal block)
	USB	2ea (Front)
	Reset	Switch (1ea)
Power Cord	2ea AC inlet	
SYSTEM		
Log	Log List	Max. 20000 (System log, Event log each)
GENERAL		
Electrical	Input Voltage / Current	100 ~ 240V AC ±10%, 50/60Hz, 4 ~ 1.5A (Dual SMPS)
Environmental	Power Consumption	Max. 56W (154 BTU with 1 HDD), Max. 170W (580 BTU with 12 HDDs)
	Operating Temperature	+0°C ~ +40°C (+32°F ~ +104°F)
Mechanical	Operating Humidity	20% ~ 85% RH
	Dimensions (WxHxD)	436.0 x 132.0 x 450.0mm (17.17" x 5.2" x 17.72") (3U)
Approvals	Weight (1x Hard Disks)	Approx. 6.7Kg (14.77 lb)
	Safety	UL, KC
	EMC	CE, FCC, CCC, Gost-R

Dimensions

Unit : mm (inch)



The Eco mark represents Samsung Techwin's will to create environment-friendly products, and indicates that the product satisfies the EU RoHS Directive.

DISTRIBUTED BY



SAMSUNG TECHWIN CO., LTD.

6, Pangyo-ro 319beon-gil, Bundang-gu, Seongnam-si, Gyeonggi-do, SEOUL 463-400 Rep. of KOREA
Tel : +82-70-7147-8741 ~ 8749, 8752 ~ 8760 Fax : +82-31-8018-3745 www.samsungsecurity.com www.samsungcctv.com
COPYRIGHT BY SAMSUNG TECHWIN. ALL RIGHT RESERVED

SAMSUNG TECHWIN AMERICA INC.
100 Challenger Rd. Suite 700 Ridgeland Park, NJ 07660
Toll Free : +1-877-213-1222 Direct : +1-201-325-6920
Fax : +1-201-373-0124

SAMSUNG TECHWIN EUROPE LTD.
2nd Floor, No. 5 The Heights, Brooklands, Weybridge,
Surrey, KT13 0NY, UK
Tel : +44-1932-82-6700 Fax : +44-1932-82-6701

SHANGHAI SAMSUNG TECHWIN CO., LTD.
32F, Bk B, International Business Center,
No. 391 Guiping Rd., Shanghai, China, 200233
Tel : +86-21-5427-1155 Fax : +86-21-5423-5122

Design and specifications are subject to change without notice.