



INCLUDED



HARDENED



FLEXIBILITY



30W POE+



ALL GIGABIT



24 + 4



The ComNet™ CNGE28FX4TX24MSPOE+ Layer 2 Managed 28 Port Ethernet Switch supports twenty-four (24) 10/100/1000 BASE-TX ports and four (4) 1000BASE-FX ports of Ethernet data. PoE+ power is available for distribution across all 24 BASE-TX ports. The four 1000BASE-FX combination ports are 1000TX or SFP\* configurable for fiber type (multimode or single-mode), connector type and distance. The exclusive C-Ring redundant ring feature protects networks from interruptions or temporary malfunctions with its fast recovery technology. The electrical ports support the 10/100/1000 Mbps Ethernet IEEE 802.3 protocol, and auto-negotiating and auto-MDI/MDIX features are included. The CNGE28FX4TX24MSPOE+ are optically (1000BASE-FX) and electrically compatible with any IEEE 802.3 compliant Ethernet device and are hardened for use in harsh operating environments.

## FEATURES

- › IEEE 802.3at Compliant for PSE. Up to 30W of PoE+ power available per port. 720W total PoE power available.
- › 56 Gbps Backplane
- › IGMP v2/v3 (IGMP snooping support) for filtering multicast traffic & Port Trunking for ease of bandwidth management
- › Supports 24 Gigabit Ports, and four 1000BASE-FX optical ports with optional ComNet SFPs
- › Power supply for switch operation and PoE power sourcing is completely self-contained within the switch
- › Fully Compliant with the Environmental Requirements of NEMA TS-1/TS-2 & the Caltrans Specification for Traffic Signal Control Equipment
- › STP/RSTP/MSTP supported
- › Windows utility, eConsole, supports centralized management, and is web-based configurable, or by Telnet and console (CLI) ports
- › Port lock to prevent access from unauthorized MAC address
- › SNMP V1/V2c/V3 for secure network management
- › Fastest Redundant Ethernet Ring: C-Ring. Recovery time <30ms over 250 switches within the ring
- › Legacy ring allows the switch to be used in an existing ring of ComNet X-Ring enabled switches
- › Low-profile 1-RU (1.75-inch) high rack-mountable chassis mounts within any standard 19-inch equipment rack
- › Operating Temperature: -40° to +75° C (-40° to +167° F). Functional to +85° C (185° F)
- › Lifetime Warranty
- › Event notification through Syslog, E-mail, SNMP trap
- › RMON for traffic monitoring
- › Supports LLDP (Link Layer Discovery Protocol)
- › PTP Client (Precision Time Protocol) for clock synchronization

## APPLICATIONS

- › HD Surveillance
- › High-Port Count Ethernet Hub Locations for Industrial Automation, Industrial Security and Transportation Networks

\* Small Form-Factor Pluggable Module. Sold separately.

## SPECIFICATIONS

### Ethernet Ports

RJ-45 Ports (24) 10/100/1000Base-TX,  
with Auto MDI/MDIX & PoE

SFP Ports (4) 1000Base-FX

### Ethernet Standards Supported

IEEE 802.3 for 10Base-T  
 IEEE 802.3u for 100Base-TX and 100Base-FX  
 IEEE 802.3z for 1000Base-X  
 IEEE 802.3ab for 1000Base-T  
 IEEE 802.3at for Power Sourcing Equipment (PSE) and PoE (up to 30 watts per port)  
 IEEE 802.3x for Flow control  
 IEEE 802.3ad for LACP (Link Aggregation Control Protocol)  
 IEEE 802.1D for STP (Spanning Tree Protocol)  
 IEEE 802.1p for COS (Class of Service)  
 IEEE 802.1Q for VLAN Tagging  
 IEEE 802.1w for RSTP (Rapid Spanning Tree Protocol)  
 IEEE 802.1s for MSTP (Multiple Spanning Tree Protocol)  
 IEEE 802.1x for Authentication  
 IEEE 802.1AB for LLDP (Link Layer Discovery Protocol)

### Switch Properties

Switching Latency 7  $\mu$ s  
 Switching Bandwidth 56 Gbps  
 Max. VLANs Available 256  
 IGMP Multicast Groups 128 for each VLAN  
 Port Rate Limiting User Defined  
 MAC Table 8000 MAC addresses available  
 Priority Queues 4  
 Processing Store-and-Forward  
 Jumbo Frame Up to 9000 Bytes

### Security Features

Device Binding Security  
 Enable/Disable Ports, MAC based port security  
 Port-Based Network Access Control: 802.1x  
 VLAN (802.1Q): To segregate and secure network traffic  
 Radius Centralized Password Management  
 SNMPv3 Encrypted Authentication and Access Security  
 SSH  
 TACACS+

### Software Features

STP/RSTP/MSTP (IEEE 802.1D/w/s)  
 C-Ring Redundant Ring: Recovery time <30ms over 250 switches in a network  
 TOS/Diffserv Supported  
 Quality of Service (802.1p) for Real-Time Traffic  
 VLAN (802.1Q) with VLAN Tagging and GVRP Supported  
 IGMP Snooping for Multicast Filtering  
 Port Configuration, Status, Statistics, Monitoring, & Security  
 DHCP Server / Client support  
 IP-Based Bandwidth Management  
 Application-Based QoS Management  
 DOS/DDOS Auto Prevention

### Network Redundancy

C-Ring  
 Legacy Ring  
 RSTP  
 STP  
 MSTP

### Alarms & Monitoring Systems

Relay Output For fault event alarming  
 Syslog Server / Client To record and view events  
 SMTP For event warning notifications via email  
 Event Selection Support  
 RS-232 Serial  
 Console DB-9 Port: RS-232 @ 115,200 bps, with console cable (included).

### LED Status Indicators

Power For AC operating power  
 System Ready Indicates switch is in the "ready" mode, or switch is upgrading firmware  
 Ring Master Indicates switch is operating in the C-Ring Master mode  
 C-Ring (Ring) Indicates switch is operating in the C-Ring mode. A flashing LED in this mode indicates the network ring has broken or faulty.  
 System Running Switch is operating continuously  
 Supervisor Log-In Switch is being accessed remotely  
 Reset to Default (DEF) Switch is reset to the default configuration  
 Ping Command to the Switch Switch is processing a Ping request  
 PoE PSE (Power Sourcing Equipment) power output  
 RJ-45 Port Bi-color LED indicates 1000 Mbps or 10/100 Mbps port/link activity  
 SFP Port Port/link activity

### Regulatory Approvals

EMI FCC Part 15, CISPR (EN55022) Class A  
 EMS EN61000-4-2  
 ESD EN61000-4-3  
 RS EN61000-4-4  
 EFT EN61000-4-5  
 Electrical Surge EN61000-4-6  
 CS EN61000-4-8, EN61000-4-11  
 Mechanical Shock IEC60068-2-27  
 Free Fall IEC60068-2-32  
 Vibration IEC60068-2-6

## SPECIFICATIONS

### Power

Operating Voltage Range	100 to 240 VAC, 50-60 Hz..
Power Consumption, Typical	36 Watts. 720 watts with 24 ports loaded with PoE+, at a maximum ambient operating temperature of +50° C. De-rate to any combination of PoE or PoE+ at a maximum PD demand of 400 watts total with 24 ports loaded, at a maximum ambient operating temperature of 75° C.

### Electrical & Mechanical

Current Protection	Overload Current Protected
Enclosure	1-RU high, 19-inch rack-mountable
Size (L×W×H)	13.46 × 16.97 × 1.73 in (34.2 × 43.1 × 4.4 cm)
Shipping Weight	<13 lbs./6 kg

### Environmental

MTBF	>100,000 hours
Operating Temp	-40° to +75° C (-40° to +167° F) Functional to +85° C
Storage Temp	-40° to +85° C (-40 to 185°F)
Relative Humidity	5% to 95% (non-condensing) <sup>1</sup>

### Compliance

Fully compliant with the environmental requirements (ambient operating temperature, storage temperature, mechanical shock, vibration, humidity with condensation, high-line/low-line voltage conditions, and voltage transient protection) of NEMA TS-1/TS-2 and the Caltrans specification for Traffic Signal Control Equipment.

[1] May be extended to humidity with condensation conditions by adding suffix 'C'



## ORDERING INFORMATION

Part Number	Description
CNGE28FX4TX24MSPOE+	(24) 10/100/1000 BASE-TX + (4) 1000BASE-FX Managed Switch with Power over Ethernet (PoE)
Options/Accessories	Add suffix 'C' for Conformally Coated Circuit Boards (Extra charge, consult factory) Rack-mount installation kit (Included) Console cable (Included) AC Power cable (Included)

NOTE: This product requires a fiber installation with a minimum 30 dB connector return loss. The use of Super Polish Connectors is recommended. Complies with FDA Performance Standard for Laser Products, Title 21, Code of Federal Regulations, Subchapter J. In a continuing effort to improve and advance technology, product specifications are subject to change without notice.

