

# MR-C10

## 19" Rack for Microtype Products



### Features

#### Robust Design

- ▶ Dedicated for Microtype products from various products series
- ▶ Mount in standard 19" cabinets, occupying 1U height
- ▶ Power supply provided
- ▶ Hot-swappable design
- ▶ Wide operating temperature range of -30 °C~60 °C

#### Compatible Microtype products

- ▶ NHD100Micro, NHD110DRMicro, FTD100Micro, FTD110DBMicro, ET1111 series, ET1111H, ET1212H and ET1100C Series

#### Warranty

- ▶ 2 year Warranty

### Description

The MR-C10 Rack is dedicated and designed for all OT Systems Microtype products. The 19" 1U-high rack conveniently houses and monitors all Microtype units. This rack option offers easy installation and instant viewing of all Microtype units' LED indicators.

The rack is powered by a 12V power supply and supports a maximum of 10 Micro units. The rack features "hot-swappable" capabilities, allowing any Microtype unit to be removed and restored without affecting the operation the units in the rack.

### Specifications

#### Electrical and Mechanical

Input Voltage	90 ~ 264VAC 46 ~ 63Hz
Input Current	1.0A@115VAC 0.5A@230VAC
Output Voltage	12 VDC
Output Current	3.34A DC (max)
Output Power	40W (max)
Efficiency (Typ.)	89%
Protections	Short circuit / Overload / Over voltage
Power Input Connector	3 pole AC inlet IEC320-C14 (Cable supplied)
Power Output Connector	Open wire for Terminal Block
Dimensions(HxWxL)	42 x 483 x 112 mm
Shipping Weight	0.7kg
No. of installation position	10

#### Environmental

Operating Temp	-40°C to +75°C
Storage Temp	-40°C to +85°C
Relative Humidity	0 to 95% non-condensing

### Ordering Information

Part Number	Description
MR-C10	1U 19" Rack for Microtype Products (includes 12V Power Adaptor)



OT Systems Ltd., May 2014

Due to continuous improvement, all product specifications are subject to change without further notice.

