

▶ 98" True 4K2K UHD Display

# QD-98



LED 

## ▶ FEATURES

- LED-backlit technology with UHD 3840 x 2160 resolution
- True 4K2K quality with refresh rates of 60Hz over DisplayPort
- 16 mm (top/right/bottom/left)
- Versatile connectivity: HDMI, DisplayPort, VGA, DVI, CVBS, Component
- Daisy chain availability: DisplayPort, RS-232 and IR
- RS-232 looping and RJ45 allow programmable remote control via computer
- IR looping allows easy operation via remote controller during multiple setting
- USB playback: USB plug and select on OSD for media content play function
- OPS slot ready for easy media player integration
- Flexible display orientation: Portrait/Landscape
- VESA mounting compliance
- Installed 8 handles at the rear of the display for easy lifting
- Built-in speakers (10Wx2)
- Durable metal housing design

## ▶ SPECIFICATION

<b>Panel</b>	Panel Type	LED-Backlit TFT LCD (IPS Panel)
	Panel Size	98"
	Max. Resolution	3840 x 2160 (UHD)
	Pixel Pitch	0.5622 mm
	Brightness	500 cd/m <sup>2</sup> (Typical)
	Contrast Ratio	1,300 : 1 (Typical)
	Viewing Angle (H/V)	178°/178°
	Display Colour	1.06 billion
	Response Time	4 ms (GTG)
<b>Input</b>	VGA	15-Pin D-Sub
	DVI	24-Pin DVI-D
	HDMI	X 3
	DisplayPort	X 1
	CVBS	RCA (Share with component Y)
	Component (YPbPr)	RCA
	USB	Type A
OPS	X 1	
<b>Output</b>	DisplayPort	X 1
<b>External Control</b>	RS-232 in/out	Phone Jack 4 pin
	RJ45	RJ45
	IR in/out	3.5Ø Jack
<b>Audio</b>	Audio In	Stereo Mini Jack X 2
	Audio Out	Stereo Mini Jack X 1
	Internal Speaker	10W X 2
	External Speaker	Jack with push button to switch Int / Ext
<b>Power</b>	Power Supply	Internal
	Power Requirements	90 – 240V, 50 – 60Hz
	Consumption	<700W (Max) <0.5W (Standby/Off)
<b>Operating Conditions</b>	Temperature	5°C ~ 40°C (41°F ~ 104°F) Landscape
		5°C ~ 35°C (41°F ~ 95°F) Portrait
	Humidity	10%~90% (No condensation)
<b>Storage Conditions</b>	Temperature	-20°C ~ 60°C (-4°F ~ 140°F)
	Humidity	10%~90% (No condensation)
<b>Mounting</b>	VESA FPMPI	Yes (M8*800 x 500 mm)
<b>Dimensions</b>	w/o base (W x H x D)	2193.2 x 1248.2 x 89.8 (Handle) /88.3 (VESA) mm (86.4" x 49.1" x 3.5")
	Packaging (W x H x D)	2503 x 1569 x 450 mm (98.5" x 61.8" x 17.7")
<b>Weight</b>	w/o base	91.4 kg (201.5 lbs)
	Packaging	132.5 kg (292.1 lbs)
<b>Accessories</b>	Supplied	CD ROM (user manual), Power cable, 15-Pin D-sub cable, Remote control, RS-232 cable

All specifications are subject to change without prior notice