

## AXIS Companion Switch 4CH

### 4-port 10/100 Mbps PoE+ switch

The palm-sized AXIS Companion Switch delivers network and power for up to 4 network cameras with Plug and Play installation. Using AXIS Companion Switch as a central power source, simplifies both installation and maintenance. The switch, together with the AXIS Companion Card 64 GB, are intended for small systems with only a few cameras and basic video storage requirements.

- > **4-port 10/100 Mbps 802.3af/at PoE+**
- > **1-port 10/100 Mbps switch**
- > **60 W PoE power budget**
- > **LED indicators for network diagnostics / PoE Status**
- > **Level VI compliant for energy efficiency**



# AXIS Companion Switch 4CH

General	
<b>Casing</b>	Metal Color: White
<b>Environment</b>	Indoor
<b>Dimensions</b>	90 x 80 x 21 mm 3.54 x 3.15 x 0.83 in
<b>Weight</b>	172 g (0.38 lb)
<b>Input power</b>	100–240 V AC, 50–60 Hz Max 62 W Power plug polarity: Center-pin positive
<b>Max. output power</b>	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3 Power over Ethernet (PoE+) IEEE 802at Type 2 Class 4 Total max 60 W 4x15 W, 2x30 W or 1x30 W + 2x15 W
<b>Connectors</b>	1x RJ45 10BASE-T/100BASE-TX 4x RJ45 10BASE-T/100BASE-TX PoE
<b>Operating conditions</b>	0 °C to 50 °C (32 °F to 122 °F) Humidity 5–95% RH (non-condensing)
<b>Storage conditions</b>	-10 °C to 70 °C (14 °F to 158 °F) Humidity 5–95% RH (non-condensing)
<b>Approvals</b>	EN 55022:2010/55032:2012 + AC : 2013 Class B

EN 55024  
EN 61000-3-2  
EN 61000-3-3  
FCC Part 15 Subpart B Class B  
ICES-003 Class B  
IEC/EN/UL 60950-1  
IEC/EN/UL 62368-1  
CE  
WEEE  
EN 50581

<b>Included accessories</b>	Installation Guide Power cord Power adapter Rubber feet (4x) Brackets (2x)
<b>Warranty</b>	Axis 3-year warranty, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>

**Environmental responsibility:**  
[www.axis.com/environmental-responsibility](http://www.axis.com/environmental-responsibility)