

AXIS A4010-E Reader

Generic touch-free reader

AXIS A4010-E Reader without Keypad is a joint cooperation between Axis and ASSA Abloy designed to perfectly match AXIS A1001 Network Door Controller. The cost-efficient reader has no keypad and its small form factor enables easy placement. Two LED symbols give clearly visible feedback. The reader supports touch-free entry with most entry card formats, and is suitable for both indoor and outdoor installation. IP65 classification makes it ready for harsh environments.

- > **Designed to perfectly match AXIS A1001**
- > **Support for most smart card formats**
- > **2 LED symbols give clearly visible feedback**
- > **Indoor and outdoor ready**
- > **IP65 classified**



AXIS A4010-E Reader

Compatible products	AXIS A1001 Network Door Controller	Storage conditions	-50 °C to 70 °C (-58 °F to 158 °F)
Indications and user interface		Approvals	EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN/IEC 61000-6-2, EN/IEC 61000-6-3, ETSI EN 300 330-2, ETSI EN 301 489-1, ETSI EN 301 489-3, CISPR 16-2-1, CISPR 16-2-3, FCC part 15 Subpart C, EN/IEC 60950-1, EN/IEC 60950-22, IC RSS-GEN, IC RSS-210, AS/NZS 4268, EN 50581 (RoHS), IEC/EN 60529 IP65
Entry authentication	Card, Tag	Dimensions	85 x 46 x 19 mm (3.35 x 1.8 x 0.75 in) Cable length: 3 m
Read range	30–40 mm with recommended cards and tags	Weight	128 g (0.28 lb)
Alarm status indication	Symbols for: Access granted, Access denied	Warranty	Axis 3-year warranty, see www.axis.com/warranty
General		Environmental responsibility:	
Casing	ABS and halogen free halon plastic	www.axis.com/environmental-responsibility	
Reader technology	MIFARE®, DESFire®, MIFARE® Classic		
Communication	RS-485 – OSDP		
Power	12–24 V DC, max 2.8 W		
Operating conditions	-30 °C to 70 °C (-34 °F to 158 °F)		