



SNCA-PS24-4E

An external power supply with one 4 Amp 24V AC fused output. Polycarbonate IP66 rated enclosure suitable for outdoor use.

Key feature: Ideal for powering 24V AC housings and the camera. This power supply must be used when a camera is in a housing of any type (dome or fixed).

This power supply is to be used with housings and camera combinations only. Please use either SNCA-PS12/1 or SNCA-PS24/1 for other cameras

SNCA-HFIXED
SNCA-HRZ25
SNCA-HRZ30
SNCA-HRX550/EXT
SNCA-HRX550/EXT/W
SNCA-HRX550/EXT/R
SNCA-HRX550/INT
SNCA-HRZ50/EXT
SNCA-HRZ50/EXT/W
SNCA-HRZ50/EXT/R
SNCA-HRZ50/INT

Supply Voltage: 230V AC 50Hz
Input connection: Internal connection, no cable supplied
Current Consumption: Approx. 100W
Colour: Grey
Size in mm (W x H x D): 160 x 235 x 125
Weight in Kg: 2.13
Packed Size in mm (W x H x D): 167 x 242 x 136
Packed Weight (Kg): 2.25
Case Material: Polycarbonate
Operating Temperature: -10°C to +50°C
Storage Temperature: -20°C to +50°C
Environmental Class: 4 (Rated for outdoor use)
MTBF: 65,000 hours
CE approved: Yes
Output Voltage: 24V AC
Output Current: 4A (fused)
Output connection: Internal connection, no cable supplied. Please use cable glands to ensure watertight seal.
IP rating: IP66 (when installed correctly)
Tamper Switch: No