



Professional Video Security Solutions

SAMSUNG DIGITAL SECURITY SYSTEMS



Camera | DVR | Network Product | Lens | Monitor | Control System | Accessories

CAMERA

| | | | | | | | | | | | | | | | | |
|--|---|---|--|---|---|--|---|--|--|--|--|--|--|--|--|---|
| FIXED CAMERA | | | | | DOMED CAMERA | | | | | | | | | | | |
| SHC-750 Extreme Ultra Low Light Camera - 1/2" Super HAD CCD, 410K pixels(N), 470K pixels(P) - Color: 550TVL, BW: 470TVL - 0.008Lux (Color), 0.0005Lux (BW) - BLC, DAN (ICR), SSNR - Privacy Masking, DS, MD | SHC-745 SV-IV Ultra Low Light High Resolution Camera - 1/2" Ev-vm CCD, 410K pixels(N), 470K pixels(P) - Color: 550TVL, BW: 700TVL, SN 52dB - 0.05Lux (Color), 0.01Lux (BW) - H.C, DAN, SSNR, Multi-language OSD - Privacy Masking, DS, MD | SHC-740 SV-III Ultra Low Light High Resolution Camera - 1/2" Super HAD CCD, 410K pixels(N), 470K pixels(P) - Color: 550TVL, BW: 570TVL - 0.08Lux (Color), 0.01Lux (BW) - H.C, DAN, SSNR, Multi-language OSD - Privacy Masking, DS, MD | SHC-735 SV-IV Ultra High Resolution WDR Camera - 1/2" Double Scan CCD, 410K pixels(N), 470K pixels(P) - Color: 550TVL, BW: 700TVL, SN 52dB - 0.3Lux (Color), 0.01Lux (BW) - 128X WDR, DAN (ICR), SSNR, Multi-language OSD - Privacy Masking, DS, MD | SVD-4600 SV-IV High Resolution WDR Vandal-Proof Dome Camera - 1/4" IT CCD, 410K pixels(N), 470K pixels(P) - Color: 550TVL, BW: 700TVL, SN 52dB - 0.2Lux (Color), 0.01Lux (BW), 3.6X (2.8 - 10mm) - 0.04Lux (Sense-up) - 128X WDR, DAN (ICR), Multi-language OSD, IP66 - SSNR, Privacy Masking, 3-Axis, DS, MD | SVD-4300 W-III 10X High Resolution Vandal-Proof Dome Camera - 1/4" IT CCD, 410K pixels(N), 470K pixels(P) - Color: 550TVL, BW: 570TVL - 0.7Lux (Color), 0.02Lux (BW) - DAN (ICR), SSNR, Decoding aluminum body - Smart Zoom, Privacy Masking, 3-Axis, MD, IP66 | SID-560/562 SV-IV High Resolution WDR Dome Camera - 1/4" Double Scan CCD, 410K pixels(N), 470K pixels(P) - Color: 550TVL, BW: 700TVL, SN 52dB - 0.15Lux (Color) - 128X WDR, DAN (ICR), Multi-language OSD - SSNR, Privacy Masking, 3-Axis, MD, DS, Dual Voltage (5/2) - DAN (ICR): SID-562, DAN: SID-560 | SID-460 W-IV High Resolution Day & Night Dome Camera - 1/2" Super HAD CCD, 410K pixels(N), 470K pixels(P) - Color: 550TVL, BW: 700TVL, SN 52dB - 0.15Lux (Color) - 0.1Lux (Color), 0.01Lux (BW), 3.6X (2.8 - 10mm) - H.C, DAN (ICR), Multi-language OSD - SSNR, Privacy Masking, 3-Axis, DS, MD | | | | | | | | | |
| SHC-730 SV-III Low Light High Resolution WDR Camera - 1/2" Super HAD CCD, 410K pixels(N), 470K pixels(P) - Color: 550TVL, BW: 570TVL - 0.13Lux (Color), 0.01Lux (BW) - 128X WDR, DAN (ICR), SSNR - Privacy Masking, MD | SDN-550 W-III High Resolution Day & Night Camera - 1/2" Super HAD CCD, 410K pixels(N), 470K pixels(P) - Color: 550TVL, BW: 570TVL - 0.3Lux (Color), 0.01Lux (BW) - Spotlight BLC, DAN (ICR), SSNR - Privacy Masking, MD | SDC-425 W-IV High Resolution Day & Night Camera - 1/2" Super HAD CCD, 410K pixels(N), 470K pixels(P) - Color: 550TVL, SN 52dB - 0.05Lux (Color) - H.C, DAN, SSNR, Multi-language OSD - Privacy Masking, DS, MD | SDC-415 W-III High Resolution Day & Night Camera - 1/2" Super HAD CCD, 410K pixels(N), 470K pixels(P) - Color: 550TVL, BW: 570TVL - 0.3Lux (Color) - BLC, DAN, SSNR - Privacy Masking, MD | SDC-313B W-III High Resolution Camera - 1/2" IT CCD, 410K pixels(N), 470K pixels(P) - Color: 550TVL, BW: 570TVL - 0.3Lux (Color) - BLC, SSNR - Privacy Masking, MD | SID-500 W-III 10X High Resolution Day & Night Dome Camera - 1/4" IT CCD, 410K pixels(N), 470K pixels(P) - Color: 550TVL, BW: 570TVL - 0.04Lux (Sense-up) - 3X (3 - 9mm), BLC, DAN, SSNR - Privacy Masking, 3-Axis, MD | SID-450/452 W-III High Resolution Day & Night Dome Camera - 1/2" Super HAD CCD, 410K pixels(N), 470K pixels(P) - Color: 550TVL, SN 52dB - 0.15Lux (Color) - Fixed 8mm, H.C, DAN, Multi-language OSD - SSNR, Privacy Masking, 3-Axis, DS, MD | SID-47 W-IV High Resolution Day & Night Dome Camera - 1/2" Super HAD CCD, 410K pixels(N), 470K pixels(P) - Color: 550TVL, SN 52dB - 0.15Lux (Color) - Fixed 8mm, H.C, DAN, Multi-language OSD - SSNR, Privacy Masking, 3-Axis, DS, MD | SID-48 W-IV High Resolution Day & Night Dome Camera - 1/2" Super HAD CCD, 410K pixels(N), 470K pixels(P) - Color: 550TVL, SN 52dB - 0.15Lux (Color) - Fixed 8mm, H.C, DAN, Multi-language OSD - SSNR, Privacy Masking, 3-Axis, DS, MD | SID-49 W-IV High Resolution Day & Night Dome Camera - 1/2" Super HAD CCD, 410K pixels(N), 470K pixels(P) - Color: 550TVL, SN 52dB - 0.3Lux (Color) - Fixed 3.7 & 8mm, H.C, DAN, Multi-language OSD - SSNR, Privacy Masking, 3-Axis, DS, MD | | | | | | | |
| ZOOM CAMERA | | | | | IR LED CAMERA | | | | | | | | | | | |
| SOC-4030 W-III High Resolution Built-in 3X Varifocal Lens Camera - 1/2" Super HAD CCD, 410K pixels(N), 470K pixels(P) - Color: 550TVL, BW: 570TVL - 0.3Lux (Color) - 3X (3 - 9mm), BLC, DAN, SSNR - Privacy Masking, MD | SDZ-375 SV-IV 37X High Resolution WDR Zoom Camera - 1/4" Double Scan CCD, 410K pixels(N), 470K pixels(P) - Color: 550TVL, BW: 480TVL, SN 52dB - 0.7Lux (Color), 0.05Lux (BW) - Optical 37X, 128X WDR, DAN (ICR), SSNR, 128 Presets - Multi-language OSD, Privacy Masking, DS, MD | SDZ-330 SV-III 30X Low Light WDR Zoom Camera - 1/4" Double Scan CCD, 410K pixels(N), 470K pixels(P) - Color: 550TVL, BW: 570TVL - 0.4Lux (Color), 0.08Lux (BW) - Optical 30X, 128X WDR, DAN (ICR), SSNR, 128 Presets - Privacy Masking, MD | SDZ-300 W-III 30X High Resolution Zoom Camera - 1/4" Super HAD CCD, 410K pixels(N), 470K pixels(P) - Color: 550TVL, BW: 570TVL - 0.6Lux (Color), 0.1Lux (BW) - Optical 30X, BLC, DAN (ICR), SSNR - Privacy Masking, DS, MD | SID-45C W-III High Resolution Day & Night Dome Camera - 1/2" Super HAD CCD, 410K pixels(N), 470K pixels(P) - Color: 550TVL, BW: 570TVL - 0.3Lux (Color) - Fixed 3.7mm, BLC, DAN, SSNR - Privacy Masking, MD | SID-46C W-III High Resolution Day & Night Dome Camera - 1/2" Super HAD CCD, 410K pixels(N), 470K pixels(P) - Color: 550TVL, BW: 570TVL - 0.3Lux (Color) - Fixed 8mm, BLC, DAN, SSNR - Privacy Masking, MD | SID-53 W-IV High Resolution Mini Dome Camera - 1/2" Super HAD CCD, 410K pixels(N), 470K pixels(P) - Color: 550TVL, SN 52dB - 0.04Lux (Sense-up) - Fixed 3mm, BLC, SSNR - Sharpness Control, Sense-up | SID-56 W-IV High Resolution Mini Dome Camera - 1/2" Super HAD CCD, 410K pixels(N), 470K pixels(P) - Color: 550TVL, SN 52dB - 0.04Lux (Sense-up) - Fixed 3mm, BLC, SSNR - Sharpness Control, Sense-up | SID-50 W-III High Resolution Mini Dome Camera - 1/2" Super HAD CCD, 410K pixels(N), 470K pixels(P) - Color: 540TVL - 0.3Lux (Color) - Fixed 3mm, BLC, SSNR - Sharpness Control, Sense-up | SPD-3750/3750T SV-IV 37X High Resolution WDR PTZ Dome Camera - 1/4" Double Scan CCD, 410K pixels(N), 470K pixels(P) - Color: 550TVL, BW: 480TVL, SN 52dB - 0.7Lux (Color), 0.05Lux (BW), Multi-language OSD - Optical 37X, 128X WDR, DAN (ICR), SSNR, 128 Presets - Privacy Masking, DS, MD, Multi-protocol * SPD-3750 related accessories are under development | SPD-3350 SV-IV 33X High Resolution WDR PTZ Dome Camera - 1/4" Double Scan CCD, 410K pixels(N), 470K pixels(P) - Color: 550TVL, SN 52dB - 0.7Lux (Color), 0.05Lux (BW), Multi-language OSD - Optical 33X, 128X WDR, DAN (ICR), SSNR, 128 Presets - Privacy Masking, DS, MD, Multi-protocol * SPD-3350 related accessories are under development | SPD-3300 SV-III 30X Low Light WDR PTZ Dome Camera - 1/4" Double Scan CCD, 410K pixels(N), 470K pixels(P) - Color: 550TVL, BW: 570TVL - 0.4Lux (Color), 0.08Lux (BW) - Optical 30X, 128X WDR, DAN (ICR), SSNR, 128 Presets - Privacy Masking, MD, Multi-protocol | SPD-3000 W-III 30X High Resolution WDR PTZ Dome Camera - 1/4" Super HAD CCD, 410K pixels(N), 470K pixels(P) - Color: 550TVL, BW: 570TVL - 0.7Lux (Color), 0.1Lux (BW) - Optical 30X, DAN (ICR), SSNR, 128 Presets - Privacy Masking, DS, MD, Multi-protocol | SPD-2300 W-III 23X High Resolution WDR PTZ Dome Camera - 1/4" Super HAD CCD, 410K pixels(N), 470K pixels(P) - Color: 550TVL, BW: 570TVL - 0.7Lux (Color), 0.1Lux (BW) - Optical 23X, DAN (ICR), SSNR, 128 Presets - Privacy Masking, DS, MD, Multi-protocol | SPD-1000 W-III 10X High Resolution Interior PTZ Dome Camera - 1/4" IT CCD, 410K pixels(N), 470K pixels(P) - Color: 550TVL, BW: 570TVL - 0.7Lux (Color), 0.1Lux (BW) - Optical 10X, DAN (ICR), SSNR, Multi-language OSD - Privacy Masking, MD, 128 Presets | SIR-4150 W-III High Resolution Day & Night IR Camera - 1/2" Super HAD CCD, 410K pixels(N), 470K pixels(P) - Color: 550TVL, BW: 570TVL - 0.1Lux (Color), 0.3Lux (Color) - 2.5X (3.8 - 9.5mm), BLC, DAN (ICR), SSNR - Privacy Masking, MD, IP65, Sun shield | SIR-4250S W-III High Resolution Day & Night IR Dome Camera - 1/2" Super HAD CCD, 410K pixels(N), 470K pixels(P) - Color: 550TVL, BW: 570TVL - 0.1Lux (Color), 0.3Lux (Color) - 2.5X (3.8 - 9.5mm), BLC, DAN, SSNR - Privacy Masking, MD, IR mode, Smoke dome cover |

DVR

| | | | | | |
|--|--|--|---|---|---|
| SVR-3200 32 Channel Premium Stand-Alone DVR - D1 (704 x 480), 400fps/P Real-time video recording - MPEG-4 Compression - Multi-streaming support - 16CH Audio recording, Emergency recording - Powerful CMS support as standard (SMM-64S) - Internal 4 HDDs, Built-in DVD writer - ATMPPOS, Built-in Web server | SVR-1680 16 Channel Premium Stand-Alone DVR - D1 (704 x 480), 400fps/P Real-time video recording - MPEG-4 Compression - Multi-streaming support - 16CH Audio recording, Emergency recording - Powerful CMS support as standard (SMM-64S) - Internal 4 HDDs, Built-in DVD writer - ATMPPOS, Built-in Web server | SVR-1660 16 Channel Stand-Alone DVR - D1 (704 x 480), 400fps/P Real-time video recording - MPEG-4 Compression - Multi-streaming support - 16CH Audio recording, Emergency recording - Powerful CMS support as standard (SMM-64S) - Internal 4 HDDs, Built-in DVD writer - ATMPPOS, Built-in Web server | SVR-1645 16 Channel Stand-Alone DVR - D1 (704 x 480), 400fps/P Real-time video recording - MPEG-4 Compression - Multi-streaming support - 16CH Audio recording, Emergency recording - Thermal / Bookmark / Calendar search - Powerful CMS support as standard (SMM-64S) - Internal 4 HDDs, Built-in DVD writer - ATMPPOS, Built-in Web server | SVR-960 9 Channel Premium Stand-Alone DVR - D1 (704 x 480), 400fps/P Real-time video recording - MPEG-4 Compression - Multi-streaming support - 16CH Audio recording, Emergency recording - Thermal / Bookmark / Calendar search - Powerful CMS support as standard (SMM-64S) - Internal 4 HDDs, Built-in DVD writer - ATMPPOS, Built-in Web server | SVR-945 9 Channel Compact Stand-Alone DVR - D1 (704 x 480), 400fps/P Real-time video recording - MPEG-4 Compression - Multi-streaming support - 16CH Audio recording, Emergency recording - Thermal / Bookmark / Calendar search - Powerful CMS support as standard (SMM-64S) - Internal 4 HDDs, Built-in DVD writer - ATMPPOS, Built-in Web server |
| SVR-1650E 16 Channel Stand-Alone DVR - D1 (704 x 480), 400fps/P Real-time video recording - MPEG-4 Compression - Multi-streaming support - 16CH Audio recording, Emergency recording - Powerful CMS support as standard (SMM-64S) - Internal 4 HDDs, Built-in DVD writer - ATMPPOS, PTZ control, Remote controller - External HDD extension units (12TB) | SVR-1640A 16 Channel Stand-Alone DVR - D1 (704 x 480), 400fps/P Real-time video recording - MPEG-4 Compression - Multi-streaming support - 16CH Audio recording, Emergency recording - Powerful CMS support as standard (SMM-64S) - Internal 4 HDDs, Built-in DVD writer - ATMPPOS, PTZ control, Remote controller - External HDD extension units (12TB) | SVR-950E 9 Channel Stand-Alone DVR - D1 (704 x 480), 400fps/P Real-time video recording - MPEG-4 Compression - Multi-streaming support - 16CH Audio recording, Emergency recording - Powerful CMS support as standard (SMM-64S) - Internal 4 HDDs, Built-in DVD writer - ATMPPOS, PTZ control, Remote controller - External HDD extension units (12TB) | SVR-940 9 Channel Stand-Alone DVR - D1 (704 x 480), 400fps/P Real-time video recording - MPEG-4 Compression - Multi-streaming support - 16CH Audio recording, Emergency recording - Thermal / Bookmark / Calendar search - Powerful CMS support as standard (SMM-64S) - Internal 4 HDDs, Built-in DVD writer - ATMPPOS, PTZ control, Remote controller - External HDD extension units (12TB) | SVR-450 4 Channel Stand-Alone DVR - D1 (704 x 480), 400fps/P Real-time video recording - MPEG-4 Compression - Multi-streaming support - 16CH Audio recording, Emergency recording - Thermal / Bookmark / Calendar search - Powerful CMS support as standard (SMM-64S) - Internal 4 HDDs, Built-in DVD writer - ATMPPOS, PTZ control, Remote controller - External HDD extension units (12TB) | SVR-440 4 Channel Stand-Alone DVR - D1 (704 x 480), 400fps/P Real-time video recording - MPEG-4 Compression - Multi-streaming support - 16CH Audio recording, Emergency recording - Thermal / Bookmark / Calendar search - Powerful CMS support as standard (SMM-64S) - Internal 4 HDDs, Built-in DVD writer - ATMPPOS, PTZ control, Remote controller - External HDD extension units (12TB) |

NETWORK PRODUCT

| | | | |
|---|---|--|---|
| SNC-570 SV-IV IPOLIS High Resolution WDR Network Camera - Real-time MPEG-4/JPEG selectable video compression - Max. 1080P (Max. 30fps) image transmission - Power over Ethernet, Bi-directional audio support - 704 x 480, 704 x 240, 352 x 240, 704 x 576, 704 x 288, 352 x 288P - 1080P, 720P, 480P, 352 x 240, 704 x 576, 704 x 288, 352 x 288P - 1080P, 720P, 480P, 352 x 240, 704 x 576, 704 x 288, 352 x 288P - 1080P, 720P, 480P, 352 x 240, 704 x 576, 704 x 288, 352 x 288P - Network Management Software / Built-in web server - 0.3Lux (Color), 0.01Lux (BW) - Privacy Masking, MD | SNC-550 W-III High Resolution Day & Night Network Camera - Real-time MPEG-4/JPEG selectable video compression - Max. 1080P (Max. 30fps) image transmission - Bi-directional audio support - 704 x 480, 704 x 240, 352 x 240, 704 x 576, 704 x 288, 352 x 288P - 1080P, 720P, 480P, 352 x 240, 704 x 576, 704 x 288, 352 x 288P - 1080P, 720P, 480P, 352 x 240, 704 x 576, 704 x 288, 352 x 288P - Network Management Software / Built-in web server - 0.3Lux (Color), 0.01Lux (BW) - Privacy Masking, MD | SNP-3300A SV-III 30X Low Light WDR PTZ Network Camera - Real-time MPEG-4/JPEG selectable video compression - Max. 1080P (Max. 30fps) image transmission - Bi-directional audio support - 704 x 480, 704 x 240, 352 x 240, 704 x 576, 704 x 288, 352 x 288P - 1080P, 720P, 480P, 352 x 240, 704 x 576, 704 x 288, 352 x 288P - 1080P, 720P, 480P, 352 x 240, 704 x 576, 704 x 288, 352 x 288P - Network Management Software / Built-in web server - 0.3Lux (Color), 0.01Lux (BW) - Privacy Masking, MD | SNP-1000A W-III 10X High Resolution PTZ Network Camera - Real-time MPEG-4/JPEG selectable video compression - Max. 1080P (Max. 30fps) image transmission - Bi-directional audio support - 704 x 480, 704 x 240, 352 x 240, 704 x 576, 704 x 288, 352 x 288P - 1080P, 720P, 480P, 352 x 240, 704 x 576, 704 x 288, 352 x 288P - 1080P, 720P, 480P, 352 x 240, 704 x 576, 704 x 288, 352 x 288P - Network Management Software / Built-in web server - 0.3Lux (Color), 0.01Lux (BW) - Privacy Masking, MD |
| SNS-400 IPOLIS 4 Channel MPEG-4/JPEG Network Video Server - Real-time MPEG-4/JPEG selectable video compression - Max. 1080P (Max. 30fps) image transmission - Bi-directional audio support - Pre-allocated alarm images with USB memory - 704 x 480, 704 x 240, 352 x 240, 704 x 576, 704 x 288, 352 x 288P - 1080P, 720P, 480P, 352 x 240, 704 x 576, 704 x 288, 352 x 288P - Network Management Software / Built-in web server - 0.3Lux (Color), 0.01Lux (BW) - Privacy Masking, MD | SNS-100 IPOLIS 1 Channel MPEG-4/JPEG Network Video Server - Real-time MPEG-4/JPEG selectable video compression - Max. 1080P (Max. 30fps) image transmission - Bi-directional audio support - Pre-allocated alarm images with USB memory - 704 x 480, 704 x 240, 352 x 240, 704 x 576, 704 x 288, 352 x 288P - 1080P, 720P, 480P, 352 x 240, 704 x 576, 704 x 288, 352 x 288P - Network Management Software / Built-in web server - 0.3Lux (Color), 0.01Lux (BW) - Privacy Masking, MD | SNR-32A/16A/9A IPOLIS 32/16/9 Channel Network Recorder (Software) - MPEG-4/JPEG dual codec - 480P, 720P, 1080P image transmission - Bi-directional audio support - 1, 4, 8, 16, 32, 64, 96 Multi-screen - PTZ, Bi-directional audio, Sensor / Relay - Alarm / Event / Search - User / Permission - Unlimited pre-record registration - Network Management Software / Built-in web server - 2 sensor input, 4 alarm output | SNM-64P IPOLIS Network Integrated Management Software - Max. 128CH Real-time live monitoring - 3-Matrix connections available (Image 2 monitor) - 1, 4, 8, 16, 32, 64, 96 Multi-screen - PTZ, Bi-directional audio, Sensor / Relay - Alarm / Event / Search - User / Permission - Unlimited pre-record registration - Network Management Software / Built-in web server - 2 sensor input, 4 alarm output |

LENS

| | | | | |
|---|---|---|--|---|
| SLA-880 1/2" 10X Motorized Zoom Lens - F1.2 Video Type auto iris - Motorized zoom 8 - 80mm, C-mount - Excellent low light performance - Simple to install and adjust - Compatible with 1/2" and 1/3" CCD cameras | SLA-3580DN 1/3" Day & Night Varifocal Lens - F1.0 DC Type auto iris - Varifocal 3.5 - 8mm, CS-mount - IR-extended lens for perfect Day & Night surveillance - Extra low dispersion & Aspherical lens for clearer images - Compact design | SLA-2985D 1/3" Varifocal Lens - F1.2 DC Type auto iris - Varifocal 2.8 - 8mm, CS-mount - Excellent low light performance - Simple to install and adjust - High-quality, Compact design | SLA-2810D 1/3" Varifocal Lens - F1.2 DC Type auto iris - Varifocal 2.8 - 10mm, CS-mount - Excellent low light performance - Simple to install and adjust - High-quality, Compact design | SLA-550D 1/3" Varifocal Lens - F1.8 DC Type auto iris - Varifocal 5 - 50mm, CS-mount - Excellent low light performance - Simple to install and adjust - High-quality, Compact design |
|---|---|---|--|---|

CONTROL SYSTEM

| | | |
|---|--|---|
| SCC-3100A System Controller for Speed Dome Cameras, DVRs and Matrix Switchers - Enhanced user convenience with rearranged keypad - Centralized control of up to 255 units from a single controller - Configurable to connect multiple system controllers up to 16 units - Ergonomic design and easy-to-use keypad - 30 joystick control of PTZ functions - B&W, L&A, large character LCD display - 20 x 4 lines - Multi-protocol support | SDQ-420 Dual Color Quad Switcher - 1600 lines real-time switching (1600 lines input) - High resolution image (720 x 576) - Multiple display and action on alarm support - Individual preset function - Adjustable delay & time display - Enhanced record and playback with digital zoom - Automatic & manual pan / tilt controlling | SMX-25632 Video Matrix Switcher - Max. 256 camera input, 32 receiver output - Connects up to 32 video cards (SMX-25632) - Supports 32 input/output - Compatible to a system based on controller (SCC-3100A) - Features presentation for screen-scaled by changes - In sync signal when switching between manual and auto camera - Built-in power off for safe power supply |
|---|--|---|

MONITOR

| | | | |
|--|--|---|---|
| STM-17LA/19LA 19", 17" Security LCD Monitor - 1280 x 800/1024 Resolution - 1500 / 1300 (H x V) / 1600 / 1200 (H x V) High Contrast Ratio - 3000hrs High brightness - 5ms Response time - 2 BNC, 1 S-Video, 1 VGA input - Protecting glass - Easy to install wall mount type support | STM-17LP/19LP 19", 17" Security LCD Monitor - 1280 x 800/1024 Resolution - 1500 / 1300 (H x V) / 1600 / 1200 (H x V) High Contrast Ratio - 3000hrs High brightness - 5ms Response time - VGA input only - Protecting glass - Easy to install wall mount type support - Voltage: 12V DC | STM-21F 21" Flat Color Monitor - 21" Flat CRT monitor - NTSC/PAL multi-system - 480TVL of horizontal resolution - Video 28K reproductions, S-Video - Built-in speaker - Metal cabinet - Free voltage: 100 - 240V AC - Dimensions: 482(W) x 328(H) x 127(D) | SAM-14MV 14" Color Monitor - High Performance Resolution - Automatic color switching system (ATCSP) panel - Front Panel Control - Built-in speaker - S-Video for separate - Y/C Signals - Free voltage: 100 - 240V AC - Dimensions: 304(W) x 284(H) x 112(D) |
| STB-270PWV Wall Bracket for PTZ Domes - Can be used with the STB-330/220 housings - Easy to install, Rugged and high strength - Dimensions: 270(W) x 154(H) x 140(D)mm - 10.63"W x 6.09"H x 5.51"D | STB-30PF Ceiling Flange for PTZ Dome - Can be used with the STB-270PWV housings with a pole - Easy to install, Rugged and high strength - Dimensions: 300(W) x 140(H) x 140(D)mm - 11.81"W x 5.51"H x 5.51"D | STB-20PF Indoor Flange for PTZ Dome - Can be used to combine a camera and the STB-330PC - With the STB-270PWV housings - Easy to install, Rugged and high strength - Dimensions: 200(W) x 140(H) x 140(D)mm - 7.87"W x 5.51"H x 5.51"D | STB-330PPM Pole Mount for PTZ Dome - Can be used to install a camera and the STB-270PWV - bracket on a wall corner - Easy to install, Rugged and high strength - Dimensions: 330(W) x 185(H) x 100(D)mm - 13.00"W x 7.28"H x 3.94"D |
| STB-340PCM Corner Mount for PTZ Dome - Can be used to install a camera on a place higher above wall - Built-in hardware (S-330)SD - Dimensions: 340(W) x 185(H) x 100(D)mm - 13.39"W x 7.28"H x 3.94"D | STB-350PPM | | |