

AN bullet 2000 IR

www.boschsecurity.com



BOSCH

Invented for life



Advantage Line

These outdoor IR bullet cameras are stylish surveillance cameras that offer excellent resolution in variable lighting conditions. The high performance 960H 1/3-inch CCD sensor provides a resolution of 720TVL. The water resistant (IP66 rated) and vandal resistant (IK08 rated) housing ensures reliable video surveillance in a variety of indoor and outdoor applications. The camera is available with a 3.6 mm fixed lens. The integrated infrared LEDs provide up to 15 m (50 ft) of night vision.

Features

- ▶ Ultra high resolution 960H (1/3") sensor
- ▶ Digitally Extended Dynamic Range
- ▶ Digital noise reduction
- ▶ Integrated IR LEDs for 15 m of night vision
- ▶ Vandal and water resistant enclosure

Technical specifications

Technical specifications	
Image Sensor	960H, 1/3" CCD, sensor resolution 720TVL
System	PAL or NTSC
Total pixels (H x V)	1020 x 596 (PAL) 1020 x 508 (NTSC)
Effective pixels (H x V)	976 x 582 (PAL) 976 x 494 (NTSC)
Lens type	Fixed lens built-in
Focal length	3.6 mm
Lens aperture	F2.0
Day/Night switching	True Day/Night mechanical filter
Video Output	Composite: 1 Vpp, 75 Ohm
Supply Voltage	12 VDC
Power Consumption	370 mA (12 VDC) max.
Sync. System	Internal sync.
S/N Ratio (AGC off)	50 dB min.
Sensitivity	B/W (with IR) 0.0 lx
Electronic shutter	1/50 – 1/10,000 (PAL) 1/60 – 1/10,000 (NTSC)
IR illumination	IR LEDs, 850 nm
IR range	Up to 15 m (50 ft)
IR angle	44° / 44° (H/V)
Mounting	Cable-managed mounting bracket included
Dimensions (Ø x L)	59 x 85 mm (2.32 x 3.34 in)
Weight (including bracket)	0.54 kg (1.19 lb)
Housing	Casted / machined aluminum
Color	Camera / bracket: Black RAL9017 Sunshield: Silver grey RAL9006
Water/dust protection	IP66
Impact resistance	IK08
Operating Temperature	-30 °C to +50 °C (-22 °F to +122 °F)
Storage Temperature	-20 °C to +60 °C (-4 °F to +140 °F)
Storage Humidity	20% to 90% RH
Certifications and approvals	
Region	Certification
Europe	CE
FCC	ANSI C 63.4:2003 FCC Part 15 Subpart B Class A
UL	UL 60065, 7th Edition, 2007-12-11 CAN/CSA-C22.2 No. 60065-03, 1st Edition, 2006-04 + A1:2006
EU	EN 55022:2006/A1:2007 EN 50130-4:1995/A2:2003 EN 61000-3-3:2008
LVD	LVD 2006/95/EC EN 60065:2002+A1+A2+A11+A12
IP	IP 66

Represented by:

Americas:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: +31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:
Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:
Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
al.securitysystems@bosch.com
www.boschsecurity.com

KS C IEC 60529:2006

Ordering information

AN bullet 2000 IR (PAL)	VTI-2075-F311
AN bullet 2000 IR (NTSC)	VTI-2075-F321
AN bullet 2000 IR (PAL) China	VTI-2075-F311C