

## X-19P



LED 

A versatile display that combines hard glass protection and multiple video inputs with a distinctive metal design for modern professional environments.

Much more than a desktop monitor, the X-19P is a high-resolution 19" display with NeoV™ Optical Glass that protects the display from scratches, accidents, and incidental damage. With strong metal casing design and the flexibility of analogue, DVI, S-Video and CVBS video inputs, the X-19P provides the versatility that is essential in multi-user environments.

- > High 1280 x 1024 SXGA resolution
- > Support Full HD 1920 x 1080
- > NeoV™ Optical Glass
- > AIP technology: PIP; Built-in Image Enhancer
- > Swift 3 ms response time
- > Versatile connectivity: VGA, DVI, CVBS (RCA), S-Video, Audio in
- > Built-in speakers (1.5W x 2)
- > EcoSmart Sensor for low watt power consumption
- > Touch sensor control keys to prevent vandalism
- > Auto-adjustment for optimal settings
- > Kensington® security socket
- > VESA standard wall mount
- > Durable metal casing
- > Available colours: black, white
- > Rigorous screening of the components for mission-critical 24/7 applications



NeoV™ Optical Glass - The most trusted hard glass protection available. Only on AG Neovo displays



# X-19P


## Specifications

## X-19P

Panel	Panel Type	LED-backlit TFT LCD
	Panel Size	19.0" (482 mm)
	Max. Resolution	SXGA 1280 x 1024
	Pixel Pitch	0.294 mm
	Brightness	250 cd/m <sup>2</sup> (Typical)
	Contrast Ratio	1000:1 (Typical)
	Viewing Angle (H/V)	170°/160° (Typical)
	Display Colour Response Time	16.7M 3 ms (GTG)
Frequency (H/V)		H: 30 kHz - 82 kHz V: 56 Hz - 75 Hz
Input	VGA	15-Pin D-Sub
	DVI	24-Pin DVI-D
	CVBS	RCA
	S-Video	4-Pin mini DIN
Audio	Audio In	1 x stereo audio in for PC (audio jack, 3.5 Ø) 1 x stereo audio in for CVBS or S-Video (RCA)
	Speaker	1.5W x 2
Power	Power Supply	External
	Power Requirements Consumption	DC 12V < 22 W (On) < 0.5 W (Active Off) < 0.5 W (Off)
NeoV™ Optical Glass	Thickness	3.0 mm (0.12")
	Reflection Rate	< 1%
	Transmission Rate	> 96%
	Coating Hardness	9H
Plug & Play	VESA	DCC 2B, DCC/CI
Operating Conditions	Temperature	0°C ~ 40°C (32°F ~ 104°F)
	Humidity	10% ~ 90%
Storage Conditions	Temperature	-20°C ~ 60°C (-4°F ~ 140°F)
	Humidity	5% ~ 95%
Mounting	VESA FPMPI	Yes (100 x 100mm & 75 x 75mm)
Dimensions	Product (W x H x D)	445 x 420 x 175mm (17.5" x 16.5" x 6.9")
	Packaging (W x H x D)	538 x 525 x 228mm (21.2" x 20.7" x 9.0")
Weight	Product Weight	6.8kg (15.0lbs)
	Packaged Weight	9.6kg (21.1lbs)
Regulation Approval	Certifications & Compliance	CB, FCC, CE, GOST-R, WEEE, RoHS, REACH
Accessories	Supplied	CD ROM (user manual), power cord, power adaptor, 15-Pin D-Sub cable, audio cable



Available in black or white




NeoV™ Optical Glass and durable metal casing  
for water, dust and scratch resistance



Front-panel keypad with Input Select, Screen Menu,  
Contrast and Brightness controls for quick adjustments



Wide range of I/O connectors for flexibility and  
expandability in video installations



EcoSmart Sensor auto adjusts brightness for ultra low  
power consumption

