

LE-22



A 22” home and office LED display with OptiCom™ Technology and a height adjustable stand designed to create a comfortable viewing experience.

Built on AG Neovo’s latest OptiCom™ technology, the LE-22 effectively protects eyes from harmful blue light and reduces annoying flicker, ensuring users a more pleasant viewing experience. Featuring an LED backlight 22” widescreen display with a full HD 1920 x 1080 resolution and an IPS panel, the LE-22 ensures exceptional image clarity and accurate colour performance from all viewing angles. With a height adjustable stand to tilt, pivot, swivel, and adjust height, the LE-22 is designed for those who are looking for both value and optimal performance.

- > 22” widescreen LED display
- > LED-backlit technology with high FHD 1920 x 1080 resolution
- > Advanced OptiCom™ Technology: Anti-blue light and flicker free technologies for eye protection and viewing comfort
- > IPS panel provides consistent and accurate colour from all viewing angles
- > Slim housing design and widescreen format
- > Excellent clarity with ultrahigh 20,000,000:1 dynamic contrast ratio
- > Superior colour performance and colour contrast
- > HDMI input for Full HD connectivity with multimedia devices
- > Built-in speakers (2W x 2)
- > Height adjustable stand: tilt, pivot, swivel, height adjustable for multiple viewing options
- > Energy efficiency
- > VESA mount standard



OptiCom™ Technology- Anti-blue light and flicker free technologies for eye protection and viewing comfort

LE-22

Specifications

LE-22


Panel	Panel Type	LED-Backlit TFT LCD (IPS Panel)
	Panel Size	21.5"
	Max. Resolution	FHD 1920 x 1080
	Pixel Pitch	0.248 x 0.248
	Brightness	250cd/m ² (Typical)
	Contrast Ratio	20,000,000:1 (DCR)
	Surface Treatments	Hard Coating (3H) Anti-glare treatment
	Viewing Angle (H/V)	178°/178°
	Display Colour	16.7M
	Response Time	7ms (GTG)
Frequency (H/V)	H.Freq	30kHz – 83kHz
	V.Freq	56Hz – 76Hz
Input	VGA	15-Pin D-Sub
	DVI	24-Pin DVI
	HDMI	HDMI
Audio	Audio In	1 x stereo audio in for PC (audio jack, 3.5 Ø)
	Speaker	2W x 2
Power	Power Supply	Internal
	Power Requirements	100 – 240 V, 50-60 Hz
	Consumption	< 33W (On) < 0.5W (Stand-by) < 0.5W (Off)
Operating Conditions	Temperature	0°C ~ 40°C (32°F ~ 104°F)
	Humidity	10% ~ 85%
Mounting	VESA FPMPMI	Yes (100 x 100mm)
Stand	Tilt Capacity	-5° ~ 22°
	Swivel	±160°
	Pivot Capacity	0° ~ 90°
	Height Adjustment	0 ~ 130 mm
Dimensions	with Base (W x H x D)	509.6 x 530.6 x 244.5 mm (20.1" x 20.9" x 9.6")
	w/o Base (W x H x D)	509.6 x 310 x 49 mm (20.1" x 12.2" x 1.9")
	Packaging (W x H x D)	677 x 403 x 173 mm (26.7" x 15.9" x 6.8")
Weight	Product Weight (with base)	4.9 kg (10.8 lbs)
	Product Weight (w/o base)	2.7 kg (5.9 lbs)
	Packaging Weight	6.4 kg (14.2 lbs)
Regulation Approval	Certifications & Compliance	CB, CE, RoHs, FCC, BSMI, WEEE
Accessories	Supplied	CD ROM (user manual), warranty card, power cord, 15-Pin D-Sub cable, Audio cable



Advanced OptiCom™ Technology: Anti-blue light and flicker free for a more comfortable viewing experience



Built-in HDMI input makes the LE-22 easy to be paired with Full HD multimedia advices



IPS panel provides superb clarity from all angles



Ergonomically-designed stand allows users to tilt, pivot, swivel and adjust the height to its ideal position