

LE-27



A spacious 27” LED display built on OptiCom™ Technology and a practical height adjustment stand for home and office multimedia applications.

As eye protection is increasingly prioritized, the LE-27 is crafted with state-of-the-art OptiCom™ Technology reducing the impact on eyes from the emissions of harmful blue light and disturbing flicker. Outstanding features also include an IPS panel, full HD resolution and HDMI input for better image clarity and enhanced rich colour to the multimedia lovers. Along with a height adjustable stand that is also able to tilt, pivot and swivel, the LE-27 justifies its competence for a wide variety of home and office applications.

- > 27” widescreen LED display
- > LED-backlit technology with high FHD 1920 x 1080 resolution
- > Advanced OptiCom™ Technology: Anti-blue light and flicker free technologies for eye protection and viewing comfort
- > IPS panel provides consistent and accurate colour from all viewing angles
- > Slim housing design and widescreen format
- > Excellent clarity with ultrahigh 20,000,000:1 dynamic contrast ratio
- > Superior colour performance and colour contrast
- > HDMI input for Full HD connectivity with multimedia devices
- > Built-in speakers (2W x 2)
- > Height adjustable stand: tilt, pivot, swivel, height adjustable for multiple viewing options
- > Energy efficiency
- > VESA mount standard



OptiCom™ Technology- Anti-blue light and flicker free technologies for eye protection and viewing comfort

LE-27

Specifications

LE-27


Panel	Panel Type	LED-Backlit TFT LCD (IPS Panel)
	Panel Size	27.0"
	Max. Resolution	FHD 1920 x 1080
	Pixel Pitch	0.311 x 0.311
	Brightness	300cd/m ² (Typical)
	Contrast Ratio	20,000,000:1 (DCR)
	Surface Treatments	Hard Coating (3H) Anti-glare treatment
	Viewing Angle (H/V)	178°/178°
	Display Colour	16.7M
	Response Time	7ms (GTG)
Frequency (H/V)	H.Freq	30kHz – 83kHz
	V.Freq	56Hz – 76Hz
Input	VGA	15-Pin D-Sub
	DVI	24-Pin DVI
	HDMI	HDMI
Audio	Audio In	1 x stereo audio in for PC (audio jack, 3.5 Ø)
	Speaker	2W x 2
Power	Power Supply	Internal
	Power Requirements	100 – 240 V, 50-60 Hz
	Consumption	< 40W (On) < 0.5W (Stand-by) < 0.5W (Off)
Operating Conditions	Temperature	0°C ~ 40°C (32°F ~ 104°F)
	Humidity	10% ~ 85%
Mounting	VESA FPMPMI	Yes (100 x 100mm)
Stand	Tilt Capacity	-5° ~ 23°
	Swivel	±160°
	Pivot Capacity	0° ~ 90°
	Height Adjustment	0 ~ 130 mm
Dimensions	with Base (W x H x D)	645.3 x 569.3 x 244.5 mm (25.4" x 22.4" x 9.6")
	w/o Base (W x H x D)	645.3 x 398.6 x 56.4 mm (25.4" x 15.7" x 2.2")
	Packaging (W x H x D)	765 x 501 x 224 mm (30.1" x 19.7" x 8.8")
Weight	Product Weight (with base)	8.2 kg (18.0 lbs)
	Product Weight (w/o base)	5.6 kg (12.3 lbs)
	Packaging Weight	10.7 kg (23.5 lbs)
Regulation Approval	Certifications & Compliance	CB, CE, RoHs, FCC, BSMI, WEEE
Accessories	Supplied	CD ROM (user manual), warranty card, power cord, 15-Pin D-Sub cable, Audio cable



Advanced OptiCom™ Technology: Anti-blue light and flicker free for a more comfortable viewing experience



Built-in HDMI input makes the LE-27 easy to be paired with Full HD multimedia advices



IPS panel provides superb clarity from all angles



Ergonomically-designed stand allows users to tilt, pivot, swivel and adjust the height to its ideal position