

Scalable solution for the small to mid-market



Milestone Husky M30 is a desktop workstation with high-grade hardware, providing a high level of performance for small to mid-size installations. The unit has easy-to-use Milestone XProtect video management software preloaded and optimized hardware, making it a predictable solution to set up and use. It is simple to add cameras and expand the system over time, making the Milestone Husky M30 the right choice for now and the future.

Product highlights

Comprehensive interactive monitoring

- Interactive and multi-layered maps provide a graphical overview of the surveillance installation for prompt response
- Alarm Manager is integrated with the map function for a consolidated overview of security and system alarms
- Advanced video search tools quickly locate recordings for use as high-quality evidence
- Multi-channel, two-way audio for message broadcasts or direct communications

Easy to deploy and expand

- Automatic camera discovery detects and configures any newly added cameras
- Configuration wizards guide uers through installation with just a few clicks
- Connecting multiple Husky M30s and Husky M50s makes surveillance solution scalable

Helping you do more

- Access video remotely for faster response to incidents
- Based on testing, the hardware is optimized so you know you have the right, reliable solution for your needs
- Smoother video performance and up to 75 percent reduced CPU load with hardware accelerated decoding

Support

- Optional Milestone CARE™ Plus provides access to software updates and online services such as Customer Dashboard, Smart Connect for mobile and push notifications
- Customer Dashboard is an online system monitoring service so resellers can keep track of technical incidents in the system and proactively solve them

Milestone Husky M30 supports all Milestone clients







Milestone Mobile



XProtect®
Web Client



Specifications

Specifications	
General	Detail
Form factor	Workstation
Type of deployment	Multi-unit, unlimited number of
	servers
Dimensions	30(W)x30(D)x9(H) cm
	11.8(W)x11.8(D)x3.8(H) in
Maximum number of cameras	32 (video stream dependent)
Maximum recording rate	136 Mbit/s
Maximum local display	300 FPS @ 720p
Camera licenses included	8
Add-on camera licenses	4 pack
Number of supported servers	Unlimited
Maximum number of users	Unlimited
Dual network interface cards	Yes
CPU	i5-3610ME 2.7Ghz
Operating system support	Windows 10
Memory	8GB
Hybrid option	Yes
Storage system	Detail
Video storage	2TB / 4TB / 8TB / 12TB
	2 HDD bays, SATA
Drive type	Western Digital Purple Drives
VMS/OS storage	64GB mSATA SSD
Optional RAID storage	No
Video management system	Detail
VMS preloaded	Milestone XProtect 2016
Milestone Care Basic	Included
Milestone Care Plus	Optional
Hardware warranty	Three years included
Automatic camera discovery	Yes
Setup wizards	Yes
Supports ONVIF cameras	Yes
Codec support	H.264, MJPEG, MPEG4, MxPEG
Multiple video export formats	Yes
Pan-tilt-zoom (PTZ) support	Yes
Audio support	Yes, two-way
Third-party application support	Yes
Milestone Interconnect™ support	Yes
Customer Dashboard support	Yes ¹
Electrical	Detail
Power input	200W / 100~240V
Maximum power consumption	68-74W
Rear system I/O	
DV-UL SYSTELL I/V	2 x GbE R145
icai system 1/0	2 x GbE RJ45 4 x USB 3.0
icai system 1/0	2 x GbE RJ45 4 x USB 3.0 1 x DVI / 1 x HDMI
near system 1/0	4 x USB 3.0
icai system I/O	4 x USB 3.0 1 x DVI / 1 x HDMI
Environmental	4 x USB 3.0 1 x DVI / 1 x HDMI 1 x Line-out / MIC-in / Line-in
	4 x USB 3.0 1 x DVI / 1 x HDMI 1 x Line-out / MIC-in / Line-in 3 x COM ports
Environmental	4 x USB 3.0 1 x DVI / 1 x HDMI 1 x Line-out / MIC-in / Line-in 3 x COM ports Detail
Environmental Operation temperature Storage temperature	4 x USB 3.0 1 x DVI / 1 x HDMI 1 x Line-out / MIC-in / Line-in 3 x COM ports Detail 0~40°C
Environmental Operation temperature	4 x USB 3.0 1 x DVI / 1 x HDMI 1 x Line-out / MIC-in / Line-in 3 x COM ports Detail 0~40°C -20°C ~70°C
Environmental Operation temperature Storage temperature	4 x USB 3.0 1 x DVI / 1 x HDMI 1 x Line-out / MIC-in / Line-in 3 x COM ports Detail 0~40°C -20°C ~70°C 10~90 % relative humidity
Environmental Operation temperature Storage temperature Humidity	4 x USB 3.0 1 x DVI / 1 x HDMI 1 x Line-out / MIC-in / Line-in 3 x COM ports Detail 0~40°C -20°C ~70°C 10~90 % relative humidity (non-condensing)
Environmental Operation temperature Storage temperature Humidity Other	4 x USB 3.0 1 x DVI / 1 x HDMI 1 x Line-out / MIC-in / Line-in 3 x COM ports Detail 0~40°C -20°C ~70°C 10~90 % relative humidity (non-condensing) Detail 1 x DVI to VGA connector CE (class A), WEEE, FCC (class
Environmental Operation temperature Storage temperature Humidity Other Accessory	4 x USB 3.0 1 x DVI / 1 x HDMI 1 x Line-out / MIC-in / Line-in 3 x COM ports Detail 0~40°C -20°C ~70°C 10~90 % relative humidity (non-condensing) Detail 1 x DVI to VGA connector
Environmental Operation temperature Storage temperature Humidity Other Accessory	4 x USB 3.0 1 x DVI / 1 x HDMI 1 x Line-out / MIC-in / Line-in 3 x COM ports Detail 0~40°C -20°C ~70°C 10~90 % relative humidity (non-condensing) Detail 1 x DVI to VGA connector CE (class A), WEEE, FCC (class

¹With Milestone Care Plus

For a complete list of specifications and features, please see the full Milestone Husky comparison chart on the Milestone website.

Product specifications subject to change without notice.

About Milestone Systems

Milestone Systems is a global industry leader in open platform IP video management software, founded in 1998 and now operating as a standalone company in the Canon Group. Milestone technology is easy to manage, reliable and proven in thousands of customer installations, providing flexible choices in network hardware and integrations with other systems. Sold through partners in more than 100 countries, Milestone solutions help organizations to manage risks, protect people and assets, optimize processes and reduce costs. For more information, visit www.milestonesys.com.


Specification summary

Cameras	CPU	Storage	RAM	Codec	Operation
8 included 32 max	i5	2/4/8/12TB JBOD	8GB	H.264	24 hours

Performance

Resolution	FPS	Record always 10 cams/20 cams	Record motion 40%	Local Smart Client
1280x720	25	8 / 7 days	19 days	
1280x720	10	9 days	23 days	300 FPS @
1920×1080	10	4 days	11 days	720p
2048 x 1536	10	3 days	7 days	

Back system configuration



^{*} To use the VGA port, you must attach the provided adapter.

Ordering information

SKU	Description
HM30-2T-8	Husky M30, 2x1TB, 8 channels included, 32 max., i5, 8GB RAM
HM30-4T-8	Husky M30, 2x2TB, 8 channels included, 32 max., i5, 8GB RAM
HM30-8T-8	Husky M30, 2x4TB, 8 channels included, 32 max., i5, 8GB RAM
HM30-12T-8	Husky M30, 2x6TB, 8 channels included, 32 max., i5, 8GB RAM
HM30-4T-8H	Husky M30, 2x2TB, Hybrid, 8 IP / 16 analog channels included, 32 max., i5, 8GB RAM

Please contact your local Milestone representative to order Husky M30.

Milestone Systems HQ, DK: Tel: +45 88 300 300 Milestone Systems US: Tel: +1 503 350 1100 Milestone Systems Canada: Tel: +1 503 350 1132

Milestone Systems has 20 offices worldwide and is distributed in more than 100 countries. For more information on how to contact us and to get purchase information, please visit our website milestonesys.com.

General inquiries: info@milestonesys.com
Sales inquiries: sales@milestonesys.com