





- ► Supports Auto-Negotiation and Auto MDI/MDI-X
- ► Supports 802.3x Flow Control
- ► Fan-less design (no noise) for office environment
- ▶ Support Energy Efficient Ethernet IEEE 802.3az
- ► Plug and Play installation








#### Warranty

1-Year Warranty

#### **Typical Application**



#### **Specifications**

Ethernet	
Standards	IEEE802.3 10Base-T
	IEEE802.3u 100Base-TX
	IEEE802.3ab 1000Base-T
	IEEE802.3az Energy Efficient Ethernet
	IEEE802.3x Flow Control
Processing Type	Store-and-Forward
Forward Filter Rate	14,880pps (10Mbps)
	148,800pps (100Mbps)
	1,488,000pps (1000Mbps)
Packet Buffer Memory	1Mbit
Address Table Size	4K MAC Addresses
Connector	8 x RJ45
<b>Electrical and Mechanic</b>	c <mark>al</mark>
Input Power	12VDC, DC Socket
Power Consumption	1A, 12W (Max.)
LED Indicators	
Power	Power Status
Ethernet (Per Port)	LINK, Activity
Dimensions (W x D x H)	158 x 111 x 26 mm
Weight	0.5 Kg
Casing	Metal Case
Mounting options	Desktop



# **Specifications**

Environmental	
Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-20°C to 70°C (-4°F to 158°F)
Relative Humidity	10% to 90% non-condensing
MTBF	> 100,000 hrs

# **Regulatory Approvals**

ISO9001

FCC

CE

# **Ordering Information**

Available Model	Description			
EC8200	Econ-line Unmanaged 8-port 10/100/1000Base-TX Ethernet Switch			
Package Checklist				
<ul> <li>■ Unmanaged Network Switch</li> <li>■ 1.5A 12VDC External Power Adapter with US, UK, EU or AU type on request</li> <li>■ Quick Installation Guide</li> </ul>		x 1 x 1 x 1		

