

PM-48



LED 

A 48" slim bezel LED-backlit display tailored for indoor digital signal application, equipped with DLNA compliance, USB playback function and Anti-Burn-in™ technology.

The PM-48 is a Full HD display with slim bezel, built-in Anti-Burn-in™ technology and image enhancer which brings the improved image quality and outstanding colour performance. The USB playback function and DLNA compliance allow users to play, manage and stream the media content effortlessly through USB or Ethernet cable. Coupled with the programmable scheduler, the display is featured with automatic selective content playing and pre-set time turn-off. Furthermore, RS-232/RJ-45 remote control function enables users to control multiple displays directly from a PC. The PM-48 is ideal for digital signage application like airports, train stations, advertisements, and broadcasting environments.

- > LED-Backlit technology with Full HD resolution
- > 11.9 mm (left/right/top) and 14.7 mm (bottom) slim bezel width
- > Anti-Burn-in™ technology
- > Built-in Image Enhancer: 3D Comb Filter/ Deinterlace/ Noise Reduction
- > USB playback function
- > DLNA compliance
- > Versatile connectivity: VGA, DVI, HDMI, Composite, Component
- > RS-232 in/out, RJ45 and IR in/out for remote control
- > Built-in scheduler allows different programme scheduling
- > Built-in speakers (10W x 2)
- > Ideal for 16/7 operations




PM-48

Specifications

PM-48

Panel	Panel Type	LED-Backlit TFT LCD
	Panel Size	48"
	Max. Resolution	1920 x 1080
	Brightness	350 cd/m ²
	Contrast Ratio	4,000 : 1
	Viewing Angle (H/V)	178°/178°
	Display Colour Response Time	1.06 B 3ms
Frequency (H/V)	H.Freq	31 kHz – 92 kHz
	V.Freq	48 Hz – 85 Hz
Input	VGA	15-Pin D-Sub
	DVI	24-Pin DVI-D
	HDMI	HDMI
	Component	RCA x 3
	CVBS	RCA (share with Component -Y)
External Control	RS-232 in/out	2.5 mm Jack
	LAN	RJ45
	IR in/out	3.5 mm phone Jack
Audio	Audio In	1 x stereo audio in for PC (audio jack, 3.5 Ø) 1 x Stereo audio in (RCA)
	Audio Out Internal Speaker	1 x Stereo audio out (RCA) 10W x 2
Other Connectivity	USB Port	USB 2.0
Power	Power Supply	Internal
	Power Requirements	100 - 240V, 50 - 60Hz
	Consumption	< 132 W (On) < 0.5 W (Active off/Off)
Operating Conditions	Temperature	5°C ~ 40°C (41°F~104°F)
	Humidity	20%~80% (No condensation)
Storage Conditions	Temperature	-20°C ~ 60°C (-4°F~140°F)
	Humidity	10%~90% (No condensation)
Mounting	VESA FPM PMI	Yes (400 x 400 mm & 200 x 200 mm)
Dimensions	w/o base (W x H x D)	1081.8 x 623.4 x 59.9 mm (42.6" x 24.5" x 2.4")
	Packaging (W x H x D)	1192 x 773 x 171 mm (47.0" x 30.4" x 6.7")
Weight	w/o base	11.52 kg (25.4 lbs)
	Packaging	16.4 kg (36.2 lbs)
Regulation Approval	Certifications & Compliance	CB, CE, FCC, WEEE, RoHS, REACH, BSMI
Accessories	Supplied	User manual, Remote control, Power cord, 15-Pin D-Sub cable, RS232 cable



USB Playback for easy multimedia content presenting



Versatile connectivity: VGA, DVI, HDMI, Composite, Component



Built-in scheduler automatically activates and deactivates the PM-48 with designated input signal according to programmed schedules.



IR for remote control