

▶ 22" SECURITY LCD DISPLAY

RX-22E



LED

▶ FEATURES

- Anti-Burn-in™ technology
- NeoV™ Optical Glass
- 3D Comb Filter/ Deinterlace/ Noise Reduction/ Freeze
- BNC horizontal resolution up to 700 TV Line
- Quick signal-switching time (≤ 0.8 sec.)
- Selectable aspect ratio and zoom function for ultimate image size
- EcoSmart Sensor and ES 7.0 panel for low watt power consumption
- Backlight flicker free for eye comfortless
- Black-level alignment for presenting the detail of darkness
- Versatile inputs: VGA, DVI, CVBS (BNC x 2), HDMI, S-Video, DP & RS-232
- CVBS (BNC x 2) & Audio passive looping
- Built-in speakers(2W x2)
- Durable metal housing
- Kensington® Lock
- Rigorous screening of the components for mission-critical 24/7 applications

▶ SPECIFICATION

Panel	Panel Type	VA Panel
	Panel Size	21.5"
	Max. Resolution	FHD 1920 x 1080
	Pixel Pitch	0.2480 mm
	Brightness	250 cd/m ²
	Contrast Ratio	20,000,000 :1 (DCR)
	Viewing Angle (H/V)	178°/178°
	Display Colour	16.7M
	Response Time	5 ms
Horizontal Resolution	TV Lines	700 TVL (NTSC)
		700 TVL (PAL)
Frequency (H/V)	H. Freq	H: 15kHz - 83kHz
	V. Freq	V: 50Hz - 85Hz
Input	VGA	15-Pin D-Sub
	DVI	24-Pin DVI-D
	CVBS	BNC x 2
	S-Video	4-Pin mini DIN
	HDMI	HDMI x 1
	DisplayPort	DP 1.2 x 1
Output	CVBS	BNC x 2
External Control	RS-232	RS-232 In
	USB	FW Update Only
Audio	Audio In	Stereo audio in for PC (3.5 mm) x 1
		Stereo audio for video (RCA) x 2
	Audio Out	Stereo audio for video (RCA) x 2
	Speaker	2W x 2
Power	Power Supply	External
	Power Requirements	DC 12V
	Consumption	< 23W (On) < 0.5W (Stand-by / Off)
Operating Conditions	Temperature	0°C ~ 40°C (32°F~104°F)
	Humidity	10%~90% (No condensation)
Storage Conditions	Temperature	-20°C ~ 60°C (-4°F~140°F)
	Humidity	5%~95% (No condensation)
Mounting	VESA FPMPMI	Yes (100 x 100 mm & 75 x 75 mm)
NeoV™ Optical Glass	Thickness	3.0 mm (0.12")
	Reflection Rate	<1%
	Coating Hardness	>9H
Dimensions	Product (W x H x D)	513 x 369 x 155 mm (20.2" x 14.5" x 6.1")
	Packaging (W x H x D)	610 x 480 x 220 mm (24.0" x 18.9" x 8.7")
Weight	Product Weight	6.9 kg (15.2 lb)
	Packaged Weight	9.5 Kg (20.9 lb)
Regulation Approval	Certifications & Compliance	FCC, CB, CE, BSMI, RoHS, WEEE, REACH, CCC, CEL, GOST-R
Accessories	Supplied	Power Cord, Power Adaptor, 15-Pin D-Sub Cable, Audio Cable

All specifications are subject to change without prior notice

www.agneovo.com

Copyright © 2017 AG Neovo. All rights reserved.
The name AG Neovo is a trademark of Associated Industries China, Inc.
All other trademarks are the property of their respective owners.