

▶ 24" SECURITY LCD DISPLAY

# RX-24E



▶ FEATURES

- Anti-Burn-in™ technology
- NeoV™ Optical Glass
- 3D Comb Filter/ Deinterlace/ Noise Reduction/ Freeze
- BNC horizontal resolution up to 700 TV Line
- Quick signal-switching time (≤ 0.8 sec.)
- Selectable aspect ratio and zoom function for ultimate image size
- EcoSmart Sensor and ES 7.0 panel for low watt power consumption
- Backlight flicker free for eye comfortless
- Black-level alignment for presenting the detail of darkness
- Versatile inputs: VGA, DVI, CVBS (BNC x 2), HDMI, S-Video, DP & RS-232
- CVBS (BNC x 2) & Audio passive looping
- Built-in speakers(2W x2)
- Durable metal housing
- Kensington® Lock
- Rigorous screening of the components for mission-critical 24/7 applications

▶ SPECIFICATION

<b>Panel</b>	Panel Type	LED-Backlit TFT LCD
	Panel Size	23.6"
	Max. Resolution	FHD 1920 x 1080
	Pixel Pitch	0.2715 mm
	Brightness	250 cd/m <sup>2</sup>
	Contrast Ratio	20,000,000 :1 (DCR)
	Viewing Angle (H/V)	178°/178°
	Display Colour	16.7M
	Response Time	5 ms
<b>Horizontal Resolution</b>	TV Lines	700 TVL (NTSC)
		700 TVL (PAL)
<b>Frequency (H/V)</b>	H. Freq	H: 15kHz - 83kHz
	V. Freq	V: 50Hz - 85Hz
<b>Input</b>	VGA	15-Pin D-Sub
	DVI	24-Pin DVI-D
	CVBS	BNC x 2
	S-Video	4-Pin mini DIN
	HDMI	HDMI x 1
	DisplayPort	DP 1.2 x 1
<b>Output</b>	CVBS	BNC x 2
<b>External Control</b>	RS-232	RS-232 In
	USB	FW Update Only
<b>Audio</b>	Audio In	Stereo audio in for PC (3.5 mm) x 1
	Audio Out	Stereo audio for video (RCA) x 2
<b>Power</b>	Power Supply	External
	Power Requirements	DC 12V
	Consumption	< 25W (On) < 0.5W (Stand-by / Off)
<b>Operating Conditions</b>	Temperature	0°C ~ 40°C (32°F~104°F)
	Humidity	10%~90% (No condensation)
<b>Storage Conditions</b>	Temperature	-20°C ~ 60°C (-4°F~140°F)
	Humidity	5%~95% (No condensation)
<b>Mounting</b>	VESA FPMPMI	Yes (100 x 100 mm & 75 x 75 mm)
<b>NeoV™ Optical Glass</b>	Thickness	3.0 mm (0.12")
	Reflection Rate	<1%
	Coating Hardness	>9H
<b>Dimensions</b>	Product (W x H x D)	562 x 397 x 155 mm (22.1" x 15.6" x 6.1")
	Packaging (W x H x D)	659 x 510 x 220 mm (25.9" x 20.1" x 8.7")
<b>Weight</b>	Product Weight	7.9 kg (17.4 lb)
	Packaged Weight	10.6 Kg (23.4 lb)
<b>Regulation Approval</b>	Certifications & Compliance	FCC, CB, CE, BSMI, RoHS, WEEE, REACH, CCC, CEL, GOST-R
<b>Accessories</b>	Supplied	Power Cord, Power Adaptor, 15-Pin D-Sub Cable, Audio Cable

All specifications are subject to change without prior notice

[www.agneovo.com](http://www.agneovo.com)

Copyright © 2017 AG Neovo. All rights reserved.  
The name AG Neovo is a trademark of Associated Industries China, Inc.  
All other trademarks are the property of their respective owners.