

# 12MP Vandal Resistant IR Fisheye Camera

## DC-Y3C14WRX


- Easy installation with DirectIP NVR
- 12MP Sensor / 9.6MP (3200 x 3008) resolution
- Fixed-focal lens (f=1.98mm)
- micro SD / SDHC / SDXC, Smart Failover
- Two-way audio
- Alarm in / out
- IK10 / IP67 supports
- PoE (IEEE 802.3af Class 3), 12VDC
- Day and night (ICR)
- True wide dynamic range (WDR)
- IR LED (Distance : 15m)
- Various viewing composition, 6 dewarping view modes
- Supports ONVIF



### SPECIFICATIONS

VIDEO		
Image Sensor	1/1.7" 12MP CMOS	
Max. Resolution	3200 x 3008	
Scanning Mode	Progressive Scan	
Lens Type	Fixed-focal	
Focal Length	f = 1.98mm	
Aperture	F2.8	
Iris Control	Fixed Iris	
Angular Field of View	180° (H), 174.8° (V), 180° (D)	
Pan / Tilt Range	-	
Min. Illumination	Color : 0.2 Lux @ F2.8 B/W : 0 Lux (IR LED On)	
Dynamic Range	More than 120dB (True WDR)	
Electronic Shutter Speed	Auto / Manual (1/30 ~ 1/10000), Anti-flicker, Slow Shutter (1~1/5, 1/7.5, 1/15)	
Day and Night	IR Cut Filter with Auto Switch	
IR Distance (LEDs)	15m / 49.2ft (6ea)	
Image Setting	Configurable Exposure, White Balance, Sharpness	
Digital Noise Reduction	Configurable 2DNR/3DNR	
Backlight Compensation	On / Off / HSBC	
Image Stabilizer	-	
Privacy Masking	8 Zones	
Intelligent Video	Video Motion Detection, Active Tampering Alarm, Trip Zone	
Viewing Composition	10, 1P, 1P2R, 2P, 4R, 107R	
Video Out	-	
NETWORK		
	DirectIP Mode	Compatibility Mode
Video Compression	H.265, H.264 (MPEG-4 Part 10/AVC), M-JPEG	
Intelligent Codec	Supported	
Bitrate Control	H.264 - CBR / VBR, H.265 - CBR / VBR	
Audio Compression	G.726, G.711	
Two-way Audio	Yes	
IP Camera Protocol	DirectIP	IDIS ONVIF Profile S
Max. Frame Rate	30ips : 3200 x 3008 15ips : 3200 x 3008 (WDR)	30ips : 3200 x 3008 15ips : 3200 x 3008 (WDR)
Supported Resolution	3200 x 3008, 1600 x 1504, 800 x 752	3200 x 3008, 2400 x 2256, 3200 x 1504, 1600 x 1504, 1600 x 752, 800 x 752
Multi-video Streaming	Quadruple Streaming	Hextuple Streaming
Network Protocols	DirectIP Protocol	RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/UDP RTSP/TCP, HTTP, HTTPS, FTP, SMTP, SMT, FEN, mDNS, uPNP
Security	SSL Encryption	Multi-user Authority, IEEE 802.1x IP Filtering, HTTPS, SSL Encryption
Remote Access Client	DirectIP NVR Connection	IDIS Web, IDIS Mobile, IDIS Solution Suite
Ethernet	RJ45 (10/100/1000 BASE-T)	
Recording Session Buffer	Yes (Up to 60MB)	
Edge Storage	micro SD / SDHC / SDXC, Smart Failover	
ALARM AND EVENT		
Trigger Event	Motion Detection, Alarm In, Audio Detection, Tampering, Trip Zone	
Event Notification	Remote S/W, Email (With Image)	
Audio In / Out	Line-in 1ea + Internal Mic 1ea / Line-out 1ea	
Alarm In / Out	Input 1ea / Output 2ea	
ENVIRONMENTAL		
Vandal Resistance	IK10	
Outdoor Ready	IP67	
Operating Temperature	-10°C ~ +60°C (+14°F ~ +140°F) *Starting Up at Above 0°C (32°F)	
Operating Humidity	0% ~ 90%	
ELECTRICAL		
Power Source	12VDC, PoE (IEEE 802.3af Class 3)	
Power Consumption	12.6W	
Approvals	FCC, CE, KC	
MECHANICAL		
Dimensions	Ø155.0mm x 58.3mm (Ø6.10" x 2.29")	
Weight	0.92kg (2.03lb)	

### DIMENSIONS



### ACCESSORIES (OPTIONAL)



### ACCESSORIES CONFIGURATION TREE

