

▶ LED-Backlit Desktop Display 27" | 24" | 22"

LE-Series

A



LED



▶ Features

- LED-backlit technology with 1920x1080 resolution
- Ergonomically designed stand for viewer's comfort and multiple viewing options: tilt, pivot, swivel, height adjustment
- Flicker-free backlight and blue light reducer for eye comfort
- HDMI and DisplayPort 1.2 inputs for Full HD connectivity with multimedia devices
- Built-in speakers
- VESA mounting for flexible installation

► Specifications

		LE-27E	LE-24E	LE-22E
Panel	Panel Type	LED-Backlit TFT LCD	LED-Backlit TFT LCD	LED-Backlit TFT LCD
	Panel Size	27.0"	23.6"	21.5"
	Max. Resolution	FHD 1920 x 1080	FHD 1920 x 1080	FHD 1920 x 1080
	Pixel Pitch	0.311 mm	0.272 mm	0.248 mm
	Brightness	300 cd/m ²	250 cd/m ²	250 cd/m ²
	Contrast Ratio	20,000,000:1 (DCR)	20,000,000:1 (DCR)	20,000,000:1 (DCR)
	Viewing Angle (H/V)	170°/160°	170°/160°	170°/160°
	Display Colour	16.7 M	16.7 M	16.7 M
	Response Time	3 ms	3 ms	3 ms
Frequency (H/V)	H Freq.	30 kHz – 83 kHz	30 kHz – 83 kHz	30 kHz – 83 kHz
	V Freq.	56 Hz – 75 Hz	56 Hz – 75 Hz	56 Hz – 75 Hz
Input	VGA	15-Pin D-Sub	15-Pin D-Sub	15-Pin D-Sub
	HDMI	HDMI 1.4	HDMI 1.4	HDMI 1.4
	DisplayPort	DisplayPort 1.2	DisplayPort 1.2	DisplayPort 1.2
Audio	Audio In	Stereo audio jack for PC (3.5 mm) x 1	Stereo audio jack for PC (3.5 mm) x 1	Stereo audio jack for PC (3.5 mm) x 1
	Audio Out	Stereo audio jack (3.5 mm) x 1	Stereo audio jack (3.5 mm) x 1	Stereo audio jack (3.5 mm) x 1
	Speaker	2W X 2	2W X 2	2W X 2
Power	Power Supply	Internal	Internal	Internal
	Power Requirements	100-240 V, 50-60Hz	100-240 V, 50-60Hz	100-240 V, 50-60Hz
	Consumption	40 W (On) < 0.5 W (Off)	35 W (On) < 0.5 W (Off)	33 W (On) < 0.5 W (Off)
Operating Conditions	Temperature	0°C ~ 40°C (32°F ~ 104°F)	0°C ~ 40°C (32°F ~ 104°F)	0°C ~ 40°C (32°F ~ 104°F)
	Humidity	10%~85% (No condensation)	10%~85% (No condensation)	10%~85% (No condensation)
Storage Conditions	Temperature	-20°C ~ 60°C (-4°F ~ 140°F)	-20°C ~ 60°C (-4°F ~ 140°F)	-20°C ~ 60°C (-4°F ~ 140°F)
	Humidity	10%~85% (No condensation)	10%~85% (No condensation)	10%~85% (No condensation)
Mounting	VESA FPMPI	Yes (100 x 100 mm)	Yes (100 x 100 mm)	Yes (100 x 100 mm)
Ergonomics	Tilt	-4°~18°	-4°~18°	-4°~18°
	Pivot	0°~ 90°	0°~ 90°	0°~ 90°
	Swivel	±160°	±160°	±160°
	Height Adjustment	0-130 mm	0-130 mm	0-130 mm
Security	Kensington Security Slot™	Yes	Yes	Yes
Dimensions	w/o base (W x H x D)	642.0 x 391.4 x 64.8 mm (25.3" x 15.4" x 2.6")	566.0 x 343.2 x 50.5 mm (22.3" x 13.5" x 2.0")	505.6 x 312.2 x 50.5 mm (19.9" x 12.3" x 2.0")
	w base (W x H x D)	642.0 x 423.7 x 249.0 mm (25.3" x 16.7" x 9.8")	566.0 x 400.2 x 249.0 mm (22.3" x 15.8" x 9.8")	505.6 x 393.8 x 249.0 mm (19.9" x 15.5" x 9.8")
	Packaging (W x H x D)	758.0 x 478.0 x 312.0 mm (29.8" x 18.8" x 12.3")	650.0 x 430.0 x 292.0 mm (25.6" x 16.9" x 11.5")	590.0 x 415.0 x 282.0 mm (23.2" x 16.3" x 11.1")
Weight	w/o base	5.5 kg (12.1 lb)	4.0 kg (8.8 lb)	3.2 kg (7.0 lb)
	w base	7.9 kg (17.4 lb)	6.4 kg (14.1 lb)	5.6 kg (12.3 lb)
	Packaging	9.9 kg (21.8 lb)	8.1 kg (17.8 lb)	7.1 kg (15.6 lb)
Regulation Approval	Certifications & Compliance	CB, CE, FCC, BSMI, RoHS, WEEE, REACH	CB, CE, FCC, BSMI, RoHS, WEEE, REACH	CB, CE, FCC, BSMI, RoHS, WEEE, REACH
Accessories	Supplied	Power Cord, 15-Pin D-sub Cable, Audio Cable, Quick Start Guide, Warranty Card	Power Cord, 15-Pin D-sub Cable, Audio Cable, Quick Start Guide, Warranty Card	Power Cord, 15-Pin D-sub Cable, Audio Cable, Quick Start Guide, Warranty Card

All specifications are subject to change without prior notice