

LOC-55



With the innovative air circulation design, the AG Neovo LOC-55 display enclosure suits 55-inch displays for indoor and outdoor environments.

The AG Neovo LOC-55 display enclosure is equipped with a sturdy metal casing and has both a ventilation and a heating system. In outdoor use, it provides protection against humidity, wetness and heat as well as vandalism and theft. The LOC-55 enclosure complies with the IP54/IP65 protection standard and can be used at temperatures ranging from -20 ° to 40 °C.

- > Electromagnetic compatibility – compliant with EMC 2014/30/EU
- > Innovated air circulation system for temperature control
- > Laminated safety glass
- > Durable and quiet fans
- > Front IP 65 and back IP 54 tested and certified
- > Compatible with any standard VESA mount
- > Indoor and outdoor use

LOC-55

Specifications

LOC-55

Loading	Applicable Sizes	55", depth max. 120 mm
Power	Power Supply	230V AC/ 50Hz
	Power Consumption	min. 25W - max. 500W (without display and PC)
Temperature	Control	Industrial fans, heating module x 2, temperature control sensor x 2
	Operating Temperature	-20 °C ~ +40 °C
Exterior	Enclosure	Steel
	Glass	6,4mm laminated safety glass, Anti-reflective
	Protection Class/ IP Rating	IP65 (Front), IP54 (Back), NEMA 4
	Doors	Lock x 2, 4 keys
	Colour	Anthracite, DB 703 fine structure
Dimension	Net (WxHxD)	1410 x 881 x 200 mm
	Packaging (WxHxD)	1460 x 931 x 250 mm
Weight	Net Weight	62 Kg
	Gross Weight	69 Kg
Accessory	Included	User Manual, Coded keys, Screws, Drilling template, standard mounting kit
	Optional	Stand (LOF-55)
Packing	1 Carton	1 set
	1 Pallet	3 set



Free-standing option with two columns



Temperature control: Heating and ventilation



Door with two locks