



**75" Professional Extra Bright
Signage Displays**

PANEL

Mainboard Model	17MB120DSR4-DSOPT7
H-Freq	135 kHz
Max. Pixel Freq.	78 MHz
V-Freq	60 Hz
Size	75"
Backlight Type	DLED
Panel Technology	IPS
Panel Type	24/7
Front Type	Ultra Narrow Bezel
Orientation	Horizontal - Vertical
Resolution	3840 x 2160 (16:9) - UHD
Active Area	1650 (H) - 928 (V)
Brightness (Cd/m2)	1000
Contrast Ratio	1200:1
Dynamic Contrast Ratio	1M:1
Panel Life Time (Min.)	50.000 hrs
Viewing Angle	178°
Response Time	9 ms
Color Value	8 Bit, 16.7 M Colors
Areas of Usage	Indoor

MECHANICAL

Size	1864mm (L) x 967mm (H) x 73mm (D)
Vesa Mounting Size	600 mm(H)x 400 mm(V) M6
Bezel Width	22 mm / 16 mm / 16 mm

FEATURES

Main Features	Open Content Management Support, Scheduler, USB-Autoplay, Auto-Launch, HDMI-CEC, HDMI-Hotplug, Auto-switch on Failover, Panel Lock, OSD Rotation, NoSignalPowerOff, Screen Saver, Pixel shift, Scheduler, Videowall support, remote control via LAN, Real Time Clock
Mechanical Features	Joystick, IR Extender Support, Rocker Switch, Detachable power cable, Carrying slots, Detachable logo positioning, Internal usb cover, Cable Holder
Optional Features	OPS Compliance, IR Overlay Touch Compliance
Speaker	2x12W

ACCESSORY

Standard	QSG, Warranty Card, IB, Power Cord, Remote Control Unit, RC Battery, Mounting Kit, Extension Brackets, IR Extender Cable
----------	--

MONITOR CONNECTIVITY

RGB Input	Dsub 15 PIN VGA CON., YPbPr
RGB Output	N/A
Video Input	2xHDMI2.0, DP1.2a, 1xUSB3.0, 1xUSB2.0, 1xUSB2.0 DP1.2a, HDMI out(USB Cover)
Video Output	DP1.2a, HDMI out
Audio Input	LINE IN JACK
Audio Output	LINE OUT JACK
External Control	RS232(DSUB 9P), RJ12, Ethernet
External Sensor	N/A

WORKING CONDITIONS

Temperature Conditions	+40°C / 0°C
Humidity	90%

POWER

Power Supply	110 VAC - 240 VAC
Power Consumption (Off)	≤0.5W

CERTIFICATION

Safety	YES
EMC	YES
CB	YES
CE	YES
Reability Approval	YES

