


DS-1600KI

Detachable Network Keyboard



Key features

- 10.1" capacitive touchscreen;
- Detachable design of the touchscreen and joystick;
- Capable of decoding 2-ch at 1080P decoding; up to 16-division window display;
- Control of MVC and decoders for video decoding and output on video wall;
- PTZ control, setting and calling preset, patrol and pattern;

Available Models

DS-1600KI

	DS-1600KI
Operating System	Android 4.4
TFT LCD Screen	10.1" TFT LCD touchscreen Resolution: 1024 × 600
Joystick	4-axis joystick
Local Decoding	Local live view at 1080P/720P/HD1/BCIF/CIF/QCIF resolution, and up to 16-division window display
Two-way Audio Input	1-ch, 3.5mm connector (2.0Vp-p, >1kΩ)
Audio Output	1-ch, 3.5mm connector (2.0 Vp-p, 600 Ω)
Network Interface	10M/100M/1000M Adaptive Ethernet port
WiFi	Supported
USB Interface	USB 2.0 × 2
Video Interface	HDMI, DVI
Power Supply	12V DC /POE
Consumption	≤15W
Working Temperature	-10°C --+55°C
Working Humidity	10°C--90°C
Dimensions (W × D × H)	404 × 180 × 163 mm
Weight	1.7 Kg