

30W POWER OVER ETHERNET INJECTOR
OUTSOURCE™
30



OUTSOURCE 30 POE injector provides power to IP cameras

Compact POE injector that delivers reliable POE for IP cameras and devices

Delivers enhanced 30W POE to all 802.8af and 802.3at standard devices. OUTSOURCE 30 is GigE compatible and automatically detects compatible devices.

- | Delivers reliable remote power to IP cameras and POE devices
- | Compatible with gigabit Ethernet
- | Safety assured as POE is only enabled to compliant devices
- | 30W Power output
- | Compact, wall-mountable unit
- | Integrated overload protection
- | Sealed, fanless design for reliability

TECHNICAL SPECIFICATION

OUTSOURCE™
30

POWER	Input Voltage Maximum current	100 to 240V AC, 50 to 60Hz 0.67A
FORWARDED POE POWER	OUTSOURCE 30	30 watts (Output voltage 55V) Overload and short-circuit protection Pin Assignment and Polarity, POE output on spare pairs 7/8 (-), 4/5 (+)
POE STANDARDS	OUTSOURCE 30	IEEE 802.3af, IEEE 802.3at POE
ETHERNET INTERFACE		RJ45 Data IN port RJ45 Data & POE OUT port 10/100/1000 Base-T compatible
LED PORT INDICATORS		Yellow On Power is on Green On A remote device is connected Green Blinking Overload state or short-circuit
PHYSICAL / ENVIRONMENTAL	Dimensions Weight Mounting Operating temperature Relative humidity Compliance	L 161mm (inc mounting holes) W 52mm H 35mm 200g [7.06oz] Integral wall-mount lugs -20°C to +40°C [-4°F to 104°F] at 30W -20°C to +55°C [-4°F to 131°F] at 22.5W 10% to 90% non-condensing CE, FCC, RoHS, EN 55032 Class B, EN55024, VCCI, UL/EN/IEC 60950-1 (Ed2)
PRODUCT CODES	VOR-OS-30-UK VOR-OS-30-US VOR-OS-30-EU	OUTSOURCE 30 OUTSOURCE 30 OUTSOURCE 30 POE Injector with UK power cable POE Injector with US power cable POE Injector with EU power cable



Veracity HQ
Prestwick International Aerospace Park
4 Dow Road
Prestwick
UK
KA9 2TU
Tel +44 (0) 1292 264967

www.veracityglobal.com
sales@veracityglobal.com

See www.veracityglobal.com website
for country and region specific contacts.