

► DisplayPort 1.2 Cable with Latches, M/M, 1.5m, 4K

DP-150BK



Features

- Support video resolutions up to 4K at 60Hz
- Support HBR2 for maximum bandwidth of 21.6Gbps
- Support 30/36-bit deep color
- Allow DisplayPort Multi-Stream Transport (MST) for daisy chaining multiple monitors
- The 3µm gold-plated contacts ensure the use durability and signal reliability
- The cable includes foil and braid shielding for superior performance and reliable connectivity
- The two magnetic rings of each terminal can reduce interference



Specifications

DP-150BK

DisplayPort Version	1.2
Connector Type	DisplayPort Male to Male
Connector Housing	Nickle-plated
Contacts (pins) Plating	3µm Gold-plated
Cable OD	6.0mm
Cable Jacket	Black PVC
Cable Shield Type	Aluminum Magnesium Alloy
Insulation Material	FOPE/HDPE
Conductor Gauge/Material	30AWG/Tinned Copper.
Supported Bandwidth	21.6Gbps for HBR2 Mode
Maximum Resolution	4096 x 2160p 60Hz / 3840 x 2160p 60Hz / 1080p 3D
Operating Temperature	-20°C ~ 80°C
Storage Temperature	-20°C ~ 80°C
Length	1.5m
Quantity	120 pieces
Dimension (W x H x L)	330 x 240 x 500 mm
Packaging Weight	14.5kg