



SMT-2730PV

27" PVM with built-in 2MP camera

Benefits

- Public View Monitors can form part of your business's Crime Prevention Through Environmental Design (CPTED) strategy.
- Prevents shrinkage by showing potential thieves they are live on camera.
- Ideal for retail use at key areas such as entrances and display racks.
- Built in camera for ease of installation. No additional accessories are required except for VESA compliant mounting.
- Powerful video performance and crisp image quality with ultra low light sensitivity and wide dynamic range.
- Can be utilised for advertisement and signage. Automatically switches from slide show mode to direct live view when motion is detected.
- Fully compatible with Wisenet SSM/WAVE/ NVR, 3rd party VMS and external devices with alarm input/output, API and ONVIF.
- On screen display (OSD) messages can be customised - size, colour, position and blinking.

SMT-2730PV

DISPLAY	
Screen Size	27" LED backlight
Resolution (HxV)	1920 x 1080
Brightness	300cd/m ²
Contrast Ratio	1000:1
Aspect Ratio	16:9
Viewing Angle (H/V)	178° / 178°
Display Color	16.7 Million
Response Time	14ms
Video System	NTSC / PAL
Panel Life	30,000 h
Filter Type	3D Comb Filter / Noise Reduction / DeInterlace
Key feature	Text overlay and blinking "Recording in progress", Slide show
INTERFACE	
Display connector	1 HDMI In
Network Connector	1 RJ-45
Reset(For Cam)	Yes
Language	English, Spanish, French, German, Italian
Memory Slot	Micro SD/SDHC/SDXC (Max 256GB)
Alarm	In 1/ Out 1
Audio	-
ENVIRONMENTAL	
Operating Temperature / Humidity	0 ~ 50° C / 40°90%, 50°50%
Storage Temperature / Humidity	-20 ~ 60° C / 40°90%, 60°35%
Certification	UL, CE, FCC
ELECTRICAL	
Input Voltage	DC12V
Power Consumption	DC12V 2.5A
MECHANICAL	
Color / Material	Black / Galvanized Steel
Product dimensions(WHD) / weight	620 x 413 x 41.1mm / 8.5Kg
Bezel Size	Top/Side: 11.1mm Bottom: 65.6mm
Vesa Mounts Interface	VESA 100 x 100mm, 200 x 100mm, 200 x 200mm
CAMERA	
Imaging Device	1/2.8" 2M CMOS
Effective Pixels	1,945(H) x 1,097(V) 2.13M pixels
Min. Illumination	Colour : 0.06 Lux (1/30sec, F2.5)
Focal Length (Zoom Ratio)	4.6mm
Wide Dynamic Range	150dB
Video Compression Format	H.265 / H.264 / MJPEG
Application Programming Interface	ONVIF Profile S/G, SUNAPI (HTTP API)

* The latest product information / specification can be found at hanwha-security.com

* Design and specifications are subject to change without notice.

* Wisenet is the proprietary brand of Hanwha Techwin.

Key Features

- 1920 x 1080 (H/V) resolution
- 178° / 178° (H/V) viewing angle
- 14ms response time
- 1 HDMI In
- In 1/ Out 1 alarm
- 150db WDR
- H.265/H.264/MJPEG
- ONVIF Profile S/G, Sunapi (HTTP API)
- The PVM's camera continues to stream video to a recorder/VMS even when turning off the monitor with the remote, or when the monitor switches to slideshow mode



Dimensions

Unit:mm(inch)

